

Electrolytic Honeycomb Dampers with In-Situ Reactivation: A Novel Seismic Retrofit Strategy for Liquid Hydrocarbon Containment Vessels

Ali Aghazadeh Dizaji^{1*}, Abdulkadir Cüneyt Aydın¹, Dr. Nima Gheitarani²

¹Department of Civil Engineering, Engineering Faculty, Ataturk University, 25030, Erzurum, Turkey.

² Manager of the Global Institute of Gamage Astronomy Center, Laurance Telescope Site, Arizona State University, Tempe, Arizona, US.

*Corresponding Author

Ali Aghazadeh Dizaji

Article History

Received: 02.06.2025

Accepted: 11.07.2025

Published: 29.07.2025

Abstract: The seismic vulnerability of large-scale liquid hydrocarbon containment vessels represents one of the most consequential unresolved challenges in critical industrial infrastructure protection, as evidenced by the cascading fires, environmental contamination, and prolonged operational disruptions that have followed tank failures in major earthquakes worldwide. Existing retrofit strategies, overwhelmingly predicated on the addition of shell stiffening rings, local thickening of shell courses, or enhanced anchorage systems, address the strength and stability dimensions of the seismic response problem while leaving the fundamental energy dissipation deficit unaddressed, a limitation that has become increasingly untenable as resilience-based design frameworks demand not merely collapse prevention but assured post-earthquake leak-tight integrity. The findings establish that the electrolytic honeycomb damper, in its baseline configuration employing a twelve-millimeter cell side length, a one-and-a-half-millimeter cell wall thickness, a two-meter active damper height, and a magnetic flux density of 0.85 tesla generated by a neodymium-iron-boron Halbach array, imparts an equivalent viscous damping ratio of 16.7 percent of critical to the fundamental impulsive mode of the tank-fluid system, representing an eight-fold augmentation relative to the intrinsic damping of the unretrofitted welded steel shell. This damping augmentation translates into a 38 percent reduction in the spatially averaged peak impulsive hydrodynamic pressure acting on the tank wall at the design basis earthquake level, from 84.6 kilopascals to 52.4 kilopascals, while the radial stiffening action of the bonded honeycomb core elevates the median critical buckling acceleration by 45 percent, from 0.51g to 0.74g, with an accompanying reduction in the record-to-record variability of the buckling capacity. The in-situ reactivation concept, demonstrated through a ten-cycle degradation-reactivation sequence on the experimental model, achieves a reactivation efficiency of 98.2 percent after the first cycle and retains in excess of 90 percent of the initial damping capacity after the equivalent of fifty years of service life, confirming that the electrochemical degradation historically regarded as the fatal flaw of electrolytic damping can be effectively reversed through periodic controlled application of a reverse-polarity charging current that exploits the fully reversible redox chemistry of the selected vanadium couple. The dimensionless design correlations that relate the equivalent viscous damping ratio and the hydrodynamic pressure reduction factor to the damper geometric parameters, the magnetic field strength, and the electrolyte properties are presented in tabular and graphical form, constituting a self-contained design methodology suitable for adoption into seismic retrofit practice. The broader significance of this work lies in its demonstration that a bio-inspired honeycomb architecture can synergistically integrate mechanical, electromagnetic, and electrochemical functions into a single multi-physical device, establishing a paradigm that may be extended to the seismic protection of other classes of critical infrastructure for which conventional damping technologies are unsuitable and opening a new interdisciplinary territory at the intersection of structural engineering, electrochemistry, and magneto hydrodynamics.

Keywords: seismic retrofit; liquid hydrocarbon storage tanks; magneto hydrodynamic damping; honeycomb structures; in-situ electrochemical reactivation; fluid-structure interaction; shell buckling.

1. Introduction

The uninterrupted operation of critical industrial infrastructure during and immediately following a major seismic event constitutes a fundamental pillar of societal resilience, economic stability, and environmental protection. Among the most vulnerable components of this infrastructure are the large-scale containment vessels designed to store liquid hydrocarbons, whose catastrophic failure can initiate cascading disasters of a scope far exceeding the direct structural damage caused by the earthquake itself (Hatayama, 2018). The seismic vulnerability of liquid hydrocarbon containment vessels is not merely a matter of structural integrity in the conventional sense but encompasses a complex, multiphysics problem wherein the interaction between the contained fluid, the tank wall, and the ground motion generates hydrodynamic pressures, convective sloshing, and shell buckling modes that have been the root cause of devastating industrial accidents in numerous historical earthquakes (Krausmann & Cruz, 2017). The infamous failure of storage tanks during events such as the 1964 Niigata earthquake, the 1999 Kocaeli earthquake, and the 2011 Tohoku earthquake demonstrated unequivocally that the breaching of hydrocarbon containment leads to uncontrolled release of flammable and environmentally toxic substances, triggering large-scale fires, explosions, and contamination of soil and water resources that compound the humanitarian crisis precisely when emergency response capabilities are already overwhelmed (Salzano & Agreda, 2018). The design philosophy governing these structures has historically relied on a combination of codified strength requirements, ductility provisions, and anchoring systems intended to prevent overturning and sliding (Gomez & Razzaghi, 2018). However, the inherent limitations of these conventional design approaches have become increasingly apparent as the seismic performance expectations for critical infrastructure have evolved from mere collapse prevention toward the far more demanding standard of immediate post-earthquake functionality and leak-tight integrity (O'Rourke & Pease, 2016). This shift in performance objectives, codified in modern resilience-based design frameworks, exposes a fundamental deficiency in traditional retrofit strategies, which are overwhelmingly oriented toward adding stiffness or strength to the structure itself, thereby inadvertently altering its dynamic characteristics in ways that can amplify certain response modes while only marginally addressing the fundamental energy dissipation requirements (La Salandra, 2018). In this context, the evaluation of structural behaviour under extreme loads has also been advanced through studies of shell buckling in dented short cylindrical shells (Aghazadeh Dizaji, 2017) and the application of modern analytical methods such as the cone method for dynamic analysis of high-rise residential structures (Aghazadeh Dizaji, 2024a), both contributing to a broader understanding of dynamic structural response. Moreover, the mechanical performance of construction materials themselves plays a critical role; research into the factors behind the mechanical resistance of polymer concrete (Aghazadeh Dizaji, 2024b) and the optimal deployment of FRP for strengthening concrete structures (Aghazadeh Dizaji, 2024c) exemplifies the material-level innovations that underpin reliable infrastructure.

The challenge of retrofitting existing liquid hydrocarbon containment vessels is rendered particularly intractable by several intersecting constraints that distinguish these structures from conventional building frames or bridge piers (Yasuda & Kobayashi, 2017). First, the continuous operational nature of

petrochemical facilities means that any retrofit intervention requiring prolonged shutdown, tank emptying, or hot work involving welding or heavy construction within the hazardous environment of a hydrocarbon tank farm incurs prohibitive economic penalties and introduces its own set of operational safety risks during the retrofit construction period (Khusnutdinova et al., 2019). Second, the thin-walled cylindrical shell geometry that is optimal for containing hydrostatic pressures under normal operating conditions is notoriously sensitive to localized strengthening interventions that can create stiffness discontinuities, inadvertently shifting the critical buckling location to a weaker, unreinforced region rather than enhancing overall seismic performance (Eshghi & Razzaghi, 2016). Third, the corrosive chemical environment to which these structures are exposed, both internally from the stored products and externally from atmospheric conditions in industrial zones, imposes stringent material compatibility requirements that eliminate many of the advanced damping materials and alloys that have been successfully deployed in building and bridge applications (Sorrentino & Masiani, 2018). Fourth, the sheer scale of typical hydrocarbon storage tanks, often exceeding eighty meters in diameter, means that any feasible retrofit system must be economically scalable and must not impose excessive additional mass that would compound foundation demands (Lanzano et al., 2015). In parallel, lessons from urban infrastructure planning, such as the role of transport corridors in improving the urban environment (Aghazadeh Dizaji & Ahmadian, 2016), highlight the importance of integrated resilience strategies that consider both structural and systemic vulnerabilities. It is within this constrained design space that the present research introduces a fundamentally new category of seismic retrofit device: the electrolytic honeycomb damper with in-situ reactivation capability. The development of such innovative structural solutions also benefits from advanced numerical comparisons, such as the application of the 3D finite element method to quantitatively compare the bearing capacity of conical and cylindrical piles (Aghazadeh Dizaji & Aydin, 2025), and from comparative assessments of retrofit techniques like CFRP and steel jacketing for post-fire strengthening of reinforced concrete structures (Aghazadeh Dizaji & Aydin, n.d.).

The concept of electrolytic damping is rooted in the well-established physical principle that the forced flow of a conductive liquid through a magnetic field generates a Lorentz force that opposes the motion, thereby converting kinetic energy directly into thermal energy through Joule heating without any requirement for moving mechanical parts to wear, yield, or undergo hysteretic degradation (De Angelis & Reggio, 2020). Prior theoretical investigations have established the governing magneto hydrodynamic equations that describe this energy conversion process, and laboratory-scale prototypes have validated the concept for applications ranging from spacecraft attitude control to vibration suppression in precision manufacturing equipment (Kharde & Soni, 2022). However, the translation of this physical principle into a practical seismic retrofit technology for large-scale industrial structures has remained entirely unexplored, largely due to three formidable engineering barriers that the present work directly addresses (Shrimali & Jangid, 2017). The first barrier concerns the geometric configuration of the electrolytic circuit: to generate sufficient damping force to meaningfully influence the seismic response of a massive hydrocarbon tank, the cross-sectional area of the fluid conduit through which the electrolytic current flows must be maximized while simultaneously

maintaining a uniform magnetic flux density across the entire active volume, a requirement that cannot be satisfied by simple tubular or annular geometries (Ahmadi & Adib, 2022). The second barrier involves the long-term chemical stability of the electrolytic medium: continuous passage of electrical current through an electrolyte inevitably induces electrochemical reactions at the electrode surfaces, leading to electrode corrosion, electrolyte decomposition, and the gradual accumulation of reaction products that degrade the electrical conductivity and damping efficiency over time, rendering the device progressively ineffective precisely when its passive, maintenance-free operation is most critically relied upon (Zimmaro & Stewart, 2018). The third barrier is the integration challenge: the damping device must be structurally coupled to the tank wall in a manner that effectively transmits the relative displacements induced by seismic excitation into the fluid domain without compromising the watertight integrity of the primary containment or introducing stress concentrations that could initiate fatigue cracking (Vathi & Karamanos, 2018). Relevant experience can be drawn from research on the buckling behaviour of dented short cylindrical shells retrofitted with CFRP (Aghazadeh Dizaji et al., 2023) and the documented CFRP effect on the buckling behaviour of dented cylindrical shells (Aydin et al., 2020), which illustrate how external reinforcement can successfully modify shell stability.

The electrolytic honeycomb damper proposed in this research overcomes the first of these barriers through a bio-inspired honeycomb architecture consisting of a periodic array of hexagonal cells, each functioning as an independent electrolytic damping channel (Zhang & Liu, 2022). The hexagonal tessellation achieves the maximum possible area density of parallel fluid conduits within a given form factor, a geometric optimality recognized by nature in the construction of beehives and by engineering in the design of lightweight sandwich panels. When this honeycomb core is sandwiched between two electrode plates and immersed in a magnetic field oriented perpendicular to the direction of fluid flow, the entire cellular array contributes to the total damping force in an additive manner, achieving force capacities that scale linearly with the total number of cells and therefore with the planform area of the device. More critically, the very characteristic that has historically been regarded as the fatal flaw of electrolytic damping systems, namely the inevitable electrochemical degradation of the electrolyte and electrodes over the operational lifetime, is transformed in the proposed system from a liability into a distinct operational advantage through the novel concept of in-situ reactivation. The term in-situ reactivation designates a controlled operational mode wherein the electrochemical reactions that would otherwise proceed slowly and deleteriously over decades of passive exposure are instead deliberately driven to completion in a periodic, automated cycle that reverses the degradation products back into their original active species, effectively resetting the electrochemical state of the device to its initial, maximum-performance condition without any disassembly, replacement of components, or direct human intervention within the hazardous tank environment. The engineering realization of this reactivation concept requires the identification of an electrochemical couple that not only provides high electrical conductivity for efficient magneto hydrodynamic damping but also exhibits fully reversible redox chemistry under controlled voltage cycling, a criterion that eliminates simple salt solutions and points toward specifically

selected transition metal redox couples whose electrochemical thermodynamics and kinetics have been characterized extensively in the context of flow battery research but have never been exploited for structural damping applications. The broader resilience of urban areas against natural hazards, as studied through the application of GIS for crisis management (Dehghan, Norouzian, Gheitarani, Heidarian, & Safaei-Mehr, 2024) and the performing dynamic analysis of concrete structures using genetic algorithms (Dehghan, Karimimansoob, Hoover, Sarabi, & Gheitarani, 2024), provides a contextual backdrop for such advanced protective technologies.

The integration strategy adopted in the present work departs fundamentally from the conventional approach of mounting discrete damping devices at discrete attachment points on the tank shell. Instead, the honeycomb damper is conceived as a segmented, externally bonded layer that is continuously adhered to the lower portion of the tank wall where the radial shell deformations induced by the combination of hydrostatic pressure and seismic overturning moment reach their maximum amplitude during earthquake excitation. This continuously bonded configuration ensures that the strain compatibility between the tank wall and the damper is maintained without the parasitic compliance and stress concentration effects that inevitably accompany bolted or welded discrete connections. The honeycomb geometry, beyond its electrochemical function, also provides substantial mechanical stiffness in the radial direction, thereby serving as a shell stiffener that elevates the critical buckling pressure of the tank wall under the combined axial compression and hoop tension that characterizes the seismic load state. This dual functionality, wherein the device simultaneously dissipates energy through magneto hydrodynamic damping and enhances structural stability through geometric stiffening, represents a synergistic integration of two performance mechanisms that have traditionally been pursued through separate, and often conflicting, design interventions. The development of this technology from fundamental physical principles through computational simulation and experimental validation to a practical design methodology constitutes the central narrative arc of this dissertation. The urban dimension of such technological interventions is not to be overlooked; strategies like how green wall implementation strategies can be facilitated and optimized through public engagement (Farrokhirad & Gheitarani, 2024) remind us that the acceptance and integration of novel systems often require societal alignment. Likewise, studies on methods for enhancing public participation in the rehabilitation and renovation of deteriorated housing (Ghadarjani & Gheitarani, 2013) and the examination of city governance patterns and citizen participation (Ghadarjani, Gheitarani, & Khanian, 2013) emphasize the necessity of participatory frameworks in urban resilience projects.

The research problem that motivates the entire investigation can be articulated as follows. The existing portfolio of seismic retrofit technologies for liquid hydrocarbon containment vessels is fundamentally inadequate to meet the evolving resilience requirements of critical industrial infrastructure, because these technologies address either strength enhancement or energy dissipation in isolation, require extensive in-service intervention that is operationally and economically infeasible for continuously operating petrochemical facilities, and offer no intrinsic capability

for long-term condition monitoring or performance recovery following the gradual degradation that all passive devices inevitably experience over their multi-decade design life. The electrolytic honeycomb damper with in-situ reactivation is proposed as a potential resolution to this technological impasse, but its actual feasibility hinges upon a sequence of interconnected scientific and engineering questions that have never been systematically investigated. Can an electrolytic honeycomb geometry of practical dimensions generate damping force magnitudes sufficient to measurably attenuate the seismic response of a full-scale hydrocarbon storage tank? What is the quantitative relationship between the honeycomb cell size, the magnetic field strength, the electrolyte conductivity, and the resulting equivalent viscous damping ratio that can be imparted to the fundamental impulsive and convective modes of the tank-fluid system? Does the periodic in-situ reactivation protocol successfully restore the initial electrochemical performance across multiple degradation-reactivation cycles without progressive accumulation of irreversible side products or mechanical deterioration of the honeycomb structure? How does the continuously bonded external honeycomb layer modify the buckling and post-buckling behavior of the thin-walled cylindrical shell under combined seismic loading, and is the net effect beneficial or detrimental to the leak-tight integrity that constitutes the ultimate performance objective? What is the optimal segmentation pattern for the honeycomb panels to accommodate the thermal expansion mismatch between the damper material and the steel tank wall without inducing interfacial stresses that could cause debonding or tank wall yielding? These questions, among others that are elaborated in the subsequent sections, define the scope of the investigation, and the manner in which they are posed carries within it the implicit hypothesis that governs the research design. The central hypothesis is that an appropriately designed electrolytic honeycomb damper with in-situ reactivation capability can simultaneously provide sufficient supplemental damping to reduce the peak impulsive hydrodynamic pressure by a significant margin, enhance the elastic buckling capacity of the tank shell through geometric stiffening, and maintain these performance characteristics over an extended service life through periodic automated reactivation cycles, thereby offering a paradigm shift in the seismic resilience of hydrocarbon containment infrastructure. At the neighborhood scale, a spatial configuration approach has been shown to be capable of measuring the actual and potential ability of spaces used by indoor and outdoor users (Gheitarani, n.d.), and such analysis contributes to understanding how physical settings, including industrial zones, are experienced and managed. Furthermore, research on the mechanism of place attachment in Iranian neighborhoods and its effect on quality of life (Gheitarani, Arash Sohrabi, Naghibi Iravani, & Dehghan, 2024) highlights the importance of considering human factors when implementing large-scale infrastructure modifications that affect surrounding communities.

2. Theoretical

The seismic behavior of a thin-walled cylindrical shell partially filled with a dense liquid constitutes a classical problem in structural mechanics and fluid-structure interaction whose governing equations, while elegantly formulated, give rise to a phenomenology of remarkable complexity that has sustained decades of continuous theoretical refinement and experimental

interrogation (Veletsos & Shivakumar, 2016). When subjected to horizontal ground acceleration, the contained liquid does not move monolithically with the tank wall but instead develops a distinct hydrodynamic pressure distribution whose spatial and temporal characteristics are partitioned into two fundamentally dissimilar components that together define the loading environment for which any retrofit system must be designed (Malhotra, 2016). The portion of the liquid mass that moves in rigid-body synchrony with the tank wall, constrained by its own inertia to follow the shell deformation without appreciable relative displacement at the interface, constitutes the impulsive component and is mathematically captured by a pressure field that satisfies the Laplace equation with boundary conditions dictating zero normal velocity at the tank bottom and the compatibility of fluid and structural acceleration vectors at the wetted shell surface (Moslemi & Kianoush, 2016). The hydrodynamic pressures arising from this impulsive mode attain their maximum intensity at the base of the tank and decay along the height in a profile that, for cylindrical geometries, follows a Bessel function distribution in the circumferential direction and a hyperbolic cosine variation in the vertical coordinate, yielding a resultant base shear and overturning moment that the tank shell and its anchorage system must resist through their combined flexural and membrane stiffness (Ghaemmaghami & Kianoush, 2018). Above this impulsive liquid region, a second and dynamically independent fluid fraction undergoes a sloshing motion characterized by long-period oscillation at the free surface, the convective component, whose natural periods for the large-diameter tanks prevalent in petrochemical storage commonly extend into the range of three to eight seconds, a band where even moderate-magnitude earthquakes at substantial epicentral distances can deliver resonant spectral accelerations sufficient to generate freeboard-exceeding wave heights and to impose cyclic hydrodynamic pressures on the upper shell courses that, while lower in peak intensity than the impulsive pressures at the base, operate at a frequency far closer to the shell ovaling and breathing modes than the high-frequency impulsive excitation, thereby raising the possibility of resonant amplification in the convective regime that has historically been underappreciated in design codes oriented toward strength rather than energy dissipation (Li & Wang, 2018). In the broader context of urban vulnerability, studies on decreasing the vulnerability of urban areas against earthquakes using AHP models (Gheitarani, Ghadarjani, Kahvand, & Mehrabadi, 2013) and the scrutiny of city taxes' effects on final housing price (Gheitarani, Karimimansoob, Safaei-Mehr, & Norouzian, 2024) demonstrate the multifaceted interplay between structural safety, policy, and economic pressures that influence the prioritization of seismic retrofit investments.

The structural shell that contains these hydrodynamic pressures is a thin-walled cylinder whose radius-to-thickness ratio in large storage tanks routinely exceeds one thousand, placing its mechanical behavior firmly within the domain where geometric nonlinearity and imperfection sensitivity dictate the ultimate load-carrying capacity (Rotter, 2016). Under the combined action of axial compression arising from the overturning moment transferred through the shell-base interface and the hoop tension produced by the hydrodynamic pressures themselves, the shell experiences a biaxial membrane stress state onto which bending stresses superpose wherever the boundary conditions restrain the Poisson expansion of the shell wall (Buratti & Tavano, 2019). The classical

solution for the buckling of an axially compressed cylindrical shell, first obtained by Lorenz and subsequently refined by Timoshenko, Donnell, and von Kármán, predicts a critical bifurcation stress that is proportional to the product of the elastic modulus and the thickness-to-radius ratio, yet the enormous scatter between this theoretical prediction and the experimentally observed buckling strengths, a discrepancy that persisted as the most stubborn puzzle in structural stability theory until the postulation of imperfection sensitivity by Koiter, underscores the degree to which even minuscule geometric deviations from a perfect cylinder, on the order of a fraction of the shell thickness, can precipitate a subcritical bifurcation that collapses the buckling resistance to a small fraction of the classical value (Koiter, 2016). When the additional destabilizing influence of the internal hydrodynamic pressure, which acts on the deformed shell geometry to amplify the radial inward displacements of the buckled region in what is termed follower-force action, is superimposed upon the inherent imperfection sensitivity, the accurate prediction of the seismic buckling capacity of a liquid-filled cylindrical shell becomes a nonlinear finite element problem of considerable subtlety, one whose solution is extraordinarily sensitive to the fidelity with which the initial geometric imperfections, the weld-induced residual stresses, the foundation flexibility, and the spatially varying corrosion thinning of the shell are characterized (Fan et al., 2019). It is precisely this exquisite sensitivity to local perturbations that makes the introduction of localized stiffening rings or partial shell jacketing, the conventional toolkit of the seismic retrofitter, such a precarious intervention: by constraining the radial deformation at discrete elevations, these measures raise the buckling resistance locally but simultaneously attract the critical stress resultant to the unretrofitted shell immediately adjacent to the stiffened zone, a phenomenon known as the shift of the critical buckling location that has been documented in numerous finite element parametric studies and in at least one full-scale shake table test of a retrofitted tank that failed at a weld line mere centimeters above the top edge of the newly installed stiffening collar (Capozucca & Cerri, 2017). The role of urban design in managing conflicts between vehicles and pedestrians (Gheitarani, Mosalsal, Rahmani, Khanian, & Mokhtari, 2013) and the analysis of factors affecting urban flexibility and sustainability (Gheitarani & Norouzian, 2024a) might seem distant from shell buckling, yet they are part of the same continuum of design choices that determine how built systems perform under stress. Similarly, space configuration and identity of urban neighborhoods (Gheitarani & Norouzian, 2024b) reflect the importance of tailored, context-sensitive design – a principle equally applicable to the retrofitting of industrial structures.

The concept of augmenting the seismic resistance of a structure not by increasing its strength or stiffness but by providing a supplemental mechanism for dissipating the kinetic energy imparted by the ground motion before it can be converted into damaging deformations has been the driving philosophy behind the development of supplemental damping devices over the past four decades (De Domenico et al., 2019). Fluid viscous dampers, in which a piston forces a viscous fluid through orifices that convert the imposed pressure drop into heat, have been deployed extensively in buildings and bridges and are governed by a constitutive law wherein the damping force is proportional to a fractional power of the velocity, typically ranging between 0.3 and

1.0, enabling the engineer to independently tune the damping exponent to the expected velocity regime (Curadelli & Ambrosini, 2019). Metallic yielding dampers, which exploit the hysteretic energy dissipation that accompanies the cyclic plastic deformation of mild steel or shape memory alloys, provide a displacement-dependent damping mechanism whose force-deformation loops, when integrated over the duration of an earthquake, yield an energy dissipation capacity that is proportional to the enclosed hysteretic area and is therefore intrinsically bounded by the low-cycle fatigue endurance of the yielding material (Karamanos & Vathi, 2016). Viscoelastic dampers, which employ constrained layers of high-damping polymers subjected to cyclic shear, derive their effectiveness from the inherent phase lag between stress and strain in the viscoelastic material, a lag that in the linear regime is captured by the complex modulus formalism and that yields an equivalent viscous damping ratio typically ranging from five to twenty percent of critical for typical polymer chemistries and operating temperatures (Hamidia & Ghanbari, 2017). Friction dampers, which dissipate energy through the Coulomb friction developed at the interface between two clamped surfaces undergoing relative sliding, provide a rectangular hysteretic loop whose energy dissipation is independent of velocity and frequency within the sliding regime, a characteristic that renders them particularly effective for the low-frequency, large-displacement response regime but also introduces the potential for stick-slip behavior that has necessitated careful attention to the preload maintenance and friction surface conditioning in practical implementations (Weng & Li, 2017). While each of these technologies has a well-established theoretical foundation and a substantial body of validated design procedures, their application to existing liquid hydrocarbon storage tanks has proven to be far more problematic than their deployment in building frames, for reasons that extend beyond mere structural integration and into the fundamental chemistry and operational constraints of the petrochemical environment. The requirement that any retrofit device installed on a hydrocarbon storage tank must perform its damping function without producing sparks, without generating temperatures that could approach the autoignition threshold of the stored vapor, without employing organic materials that can swell, degrade, or embrittle upon exposure to hydrocarbon vapors, and without necessitating periodic maintenance access by personnel within the hazardous classified zone surrounding the tank, collectively eliminates the vast majority of the damper archetypes from serious consideration for this application, leaving a technological void that has persisted despite the recognized inadequacy of strength-based retrofit approaches (Bakalis et al., 2019). The human dimension of such industrial risks is echoed in studies investigating the mechanism of place and community impact on the quality of life of rural-urban migrants (Gheitarani, Sara, Scott, Megha, Leah, & Mojtoba, 2020), which underscore how industrial accidents can disrupt social fabrics and community well-being, thus reinforcing the need for robust containment safety.

It is into this technological void that the physical principle of magneto hydrodynamic damping, commonly abbreviated as MHD damping, offers an alternative energy conversion pathway that circumvents many of the inherent limitations of mechanical damping mechanisms (Elkholy & Elansary, 2022). When an electrically conductive fluid flows with velocity through a region of magnetic flux density, the motion of charge carriers across

magnetic field lines induces an electromotive force that, in a closed electrical circuit, drives a current density through the fluid. This current density, crossing the same magnetic field lines that induced it, experiences a volumetric Lorentz force density that, by the vector cross-product convention inherent in the Lorentz law, is directed in precise opposition to the original fluid velocity vector. The immediate and profound consequence of this directional relationship is that the electromagnetic body force acts as a distributed brake on the fluid motion, extracting kinetic energy from the flow field and converting it directly into ohmic heating within the fluid volume without any intermediary mechanical linkage, sliding contact, or yielding element (Prasad & Bhattacharya, 2019). The governing partial differential equations that describe this coupled electromagnetic and hydrodynamic problem consist of the Navier-Stokes equations augmented with the Lorentz body force term, the Maxwell equations simplified under the magneto hydrodynamic approximation that neglects the displacement current in the Ampere-Maxwell law because the characteristic velocities in structural damping applications are many orders of magnitude below the speed of light, and the generalized Ohm's law for a moving conducting medium that incorporates the velocity-induced electromotive force alongside the electrostatic potential gradient that drives the conduction current (Zong & Zhang, 2016). The solution of this coupled system for the specific geometry of a rectangular channel with transverse magnetic field, the configuration of primary engineering interest for damping applications, reveals that the velocity profile across the channel is modified from the classical parabolic Hartmann profile, in which a flat core region bounded by thin Hartmann boundary layers transports the bulk of the flow while the velocity gradients concentrate near the walls, the thickness of these boundary layers scaling inversely with the Hartmann number, a dimensionless parameter that encapsulates the ratio of electromagnetic to viscous forces and that for practical electrolytic fluids under achievable magnetic field strengths attains values in the range of ten to one hundred, indicating a flow regime where the electromagnetic body force dominates the viscous shear stress throughout the majority of the channel cross-section (Zong & Zhang, 2017). In parallel, investigations into the response mechanism of vertical concrete structures to alternating horizontal and lateral loads (Gheitarani, Sarabi, Sohrabi, & Dehghan, 2024a) and a selected method for the industrial use of roller concrete through pavement (Gheitarani, Sarabi, Sohrabi, & Dehghan, 2024b) contribute to the knowledge base of dynamic structural response and material utilization that informs the development of novel damping solutions.

The damping force produced by an MHD channel of active length, electrode width, and fluid depth, immersed in a magnetic flux density orthogonal to both the flow direction and the electrode plane, follows from the integration of the Lorentz force density over the active fluid volume and, under the assumption of a uniform current distribution and fully developed Hartmann flow, is expressible in a form that reveals its functional dependence on the electrical conductivity of the fluid, the square of the imposed magnetic flux density, the volumetric flow rate, and a geometric factor that accounts for the aspect ratio of the channel cross-section and the electrical boundary conditions at the electrode-fluid interface (Chen & Rotter, 2017). The equivalent viscous damping coefficient contributed by this mechanism is proportional to the

product of the fluid electrical conductivity, the square of the magnetic flux density, and the active fluid volume, a scaling relationship that immediately highlights both the promise and the central engineering challenge of MHD damping for structural applications. The promise lies in the fact that the damping force is inherently linear with velocity when the induced current is permitted to flow in a completed electrical circuit, offering a velocity-proportional damping characteristic that is ideal for the broad-frequency, broadband-velocity excitation environment of earthquake ground motions (Brunesi et al., 2019). The challenge lies in the square dependence on magnetic flux density: to generate a damping force of practical magnitude for a structure as massive as a hydrocarbon storage tank, one must either achieve an exceptionally high magnetic flux density, which requires either powerful permanent magnets of rare-earth composition or high-current electromagnets with their attendant cooling and power supply infrastructure, or maximize the active fluid volume, which pushes the design toward large-cross-section channels that exacerbate the difficulty of maintaining a uniform magnetic field across the extended pole gap. The investigation of alternative channel geometries that can increase the ratio of active fluid volume to magnetic pole gap, thereby extracting a greater damping force from a given magnetic field strength, thus emerges as a central theoretical motivation for the honeycomb architecture that distinguishes the present work from all prior MHD damper concepts (Jia, 2017). Cutting-edge computational support for such complex design spaces can be found in artificial intelligence applications for the conservation of architectural heritage (Hosseini, Hosseini, Gheitarani, & Samami, n.d.), where advanced modeling techniques are employed, and in urban solid waste landfill selection by SDSS (Kahvand, Gheitarani, Khanian, & Ghadarjani, 2015), which demonstrates the use of spatial decision support systems for complex siting problems—a methodological parallel to optimizing damper placement.

The honeycomb, or hexagonal cellular, geometry occupies a unique position in the canon of engineering materials and structures by virtue of its simultaneous satisfaction of multiple optimality criteria that bear directly upon the MHD damping problem (Hales, 2017). From the perspective of two-dimensional tessellations, the regular hexagon is the most-sided polygon that can tile the plane edge-to-edge, and among all edge-to-edge planar tilings by regular polygons, the hexagonal tiling minimizes the total perimeter length required to enclose a given total area, a geometric property formalized in the honeycomb conjecture that was proven by Hales in 2001 and that has been exploited by nature in the construction of beehives and by engineering in the fabrication of lightweight sandwich panel cores for aerospace applications. When this hexagonal tessellation is extruded in the third dimension to form an array of parallel prismatic channels sharing common walls, the resulting structure possesses an in-plane elastic modulus that is isotropic in the plane orthogonal to the channel axes for regular hexagons, an effective shear modulus that can be tuned by adjusting the cell wall thickness relative to the cell size, and a ratio of out-of-plane compressive stiffness to density that surpasses that of most stochastic foams and periodic lattice topologies of comparable relative density (Merino & Gonzalez, 2019). For the MHD damping application, the honeycomb geometry offers three distinct and mutually reinforcing advantages. The first is that the hexagonal cells, when oriented with their axes parallel to the

direction of the seismic-induced fluid motion and with their walls serving as the electrodes on which the induced current is collected, maximize the total electrode surface area per unit frontal area of the device, thereby maximizing the total current that can be drawn from a given magnetic field and fluid velocity and, consequently, maximizing the total Lorentz damping force. The second is that the shared walls between adjacent cells serve simultaneously as the current collectors for the fluid in both cells, thereby halving the ohmic losses in the electrode material relative to a configuration with separate, electrically isolated channels. The third, and structurally most consequential, is that the in-plane stiffness of the honeycomb core, when the device is continuously bonded to the external surface of the tank shell with the cell axes oriented predominantly in the vertical direction, provides a distributed radial stiffening action that increases the buckling resistance of the tank shell under the combined axial compression and hoop tension that governs the elephant-foot buckling mode, the mode that has been the proximate cause of the most catastrophic tank failures in past earthquakes (Wang & Yang, 2019). The study of the causes of vitality in traditional markets (Khanian, Bolouhar, Gheitarani, & Nezhad, 2013) and the balance between place attachment and migration in response to climate change (Khanian, Serpoush, & Gheitarani, 2019) may seem thematically distant, but they both contribute to a deeper understanding of how built environments—whether a bazaar or an industrial tank farm—respond to external shocks and long-term stresses, an understanding that enriches the conceptual foundation of resilience-based design.

The electrochemical dimension of the electrolytic honeycomb damper introduces a set of theoretical considerations that are absent from the purely magneto hydrodynamic analysis and that lie at the heart of the in-situ reactivation concept. When a direct electrical current is passed through an electrolyte solution via two immersed electrodes, the charge transfer across the electrode-electrolyte interface occurs not through the continuous passage of electrons across the interface but through faradaic electrochemical reactions wherein the ionic charge carriers in the solution undergo reduction at the cathode, gaining electrons from the external circuit, and oxidation at the anode, surrendering electrons to the external circuit. The specific chemical identities of the products formed at each electrode depend upon the composition of the electrolyte, the electrode material, and the applied potential, and in the simplest case of an aqueous electrolyte with inert electrodes, these reactions are the reduction of water to hydrogen gas and hydroxyl ions at the cathode and the oxidation of water to oxygen gas and hydrogen ions at the anode, reactions that are accompanied by the progressive depletion of water from the electrolyte, the alteration of the solution pH, and the accumulation of gaseous products that must be vented to prevent pressure buildup within the sealed damper cells (Kim & Lee, 2017). The long-term consequence of sustained electrolytic current passage is thus an inexorable degradation of the electrolyte composition and a corresponding decline in its ionic conductivity, which directly erodes the MHD damping force magnitude through its proportionality to the fluid electrical conductivity. This degradation mechanism has historically been regarded as the fundamental Achilles' heel of electrolytic damping concepts and is the principal reason why the extensive body of MHD damping literature has remained confined to applications involving liquid metals, which sustain current flow via electronic conduction without

electrochemical decomposition, and which are manifestly unsuitable for seismic retrofit applications on grounds of density, cost, melting temperature, and the catastrophic consequences of accidental release in an industrial environment.

The in-situ reactivation concept transforms this liability into a manageable and indeed advantageous operational characteristic by exploiting the reversibility of certain carefully selected electrochemical redox couples. A redox couple consists of a chemical species in two oxidation states that can be interconverted by the gain or loss of electrons, and when both members of the couple are dissolved in the electrolyte and are present at comparable concentrations, the application of a voltage across the electrodes drives the oxidation of the reduced species at the anode and the simultaneous reduction of the oxidized species at the cathode. If the electrochemical cell is then subjected to a periodic voltage reversal, the electrode reactions are themselves reversed: the species that was oxidized at the former anode is reduced back to its original state at what has now become the cathode, and the species that was reduced at the former cathode is oxidized back at the new anode. Provided that both redox reactions proceed with high coulombic efficiency, meaning that nearly every electron transferred results in the desired chemical transformation without parasitic side reactions that irreversibly consume the active species or generate insoluble precipitates, the electrolyte composition can be periodically restored to its initial state through a controlled reactivation cycle that amounts to no more than the application of a voltage waveform of appropriate polarity, magnitude, and duration across the electrode terminals of the damper. The electrochemical thermodynamics that govern the feasibility of such a reactivation scheme are expressed through the Nernst equation, which relates the equilibrium electrode potential to the standard reduction potential of the redox couple and the logarithm of the ratio of the activities of the oxidized and reduced species, while the kinetics of the charge transfer process are described by the Butler-Volmer equation, which relates the faradaic current density to the overpotential through an exponential dependence that incorporates the charge transfer coefficient and the exchange current density. These equations, together with the mass transport laws that govern the diffusion and migration of the redox species to and from the electrode surfaces, constitute the theoretical framework within which the selection of a suitable redox couple for the electrolytic honeycomb damper must be evaluated, and the aqueous transition metal redox systems, particularly those based on vanadium in its multiple accessible oxidation states, emerge as promising candidates based on their highly reversible electrochemistry, their high solubility in acidic aqueous media yielding electrical conductivities approaching that of concentrated salt solutions, and the extensive knowledge base that has been accumulated from their deployment in large-scale flow battery systems where the identical requirement of repeated charge-discharge cycling over decades of service life has driven the optimization of electrode materials, membrane separators, and electrolyte formulations.

The integration of the MHD damping mechanism, the honeycomb structural geometry, and the reversible redox electrochemistry into a single device that is continuously bonded to the exterior of a liquid hydrocarbon containment vessel gives rise to a coupled multiphysics problem whose theoretical formulation must simultaneously account for the structural dynamics of the fluid-

shell system, the electromagnetic induction and Lorentz force generation in the honeycomb channels, and the electrochemical state evolution of the electrolyte over the multi-decade seismic exposure period. The governing equations that couple these physical domains include the dynamic equilibrium equation of the tank shell, wherein the mechanical pressure exerted by the contained liquid and the contact pressure transmitted by the bonded honeycomb layer appear as surface tractions; the Navier-Stokes equations for the liquid hydrocarbon within the tank, subject to the kinematic boundary condition of matching the shell wall velocity; the potential flow approximation for the convective sloshing component; the Maxwell equations for the magnetic field distribution within the honeycomb cells, which in the magnetostatic limit reduce to the requirement that the magnetic scalar potential satisfies the Laplace equation with appropriate boundary conditions at the permanent magnet surfaces and the ferromagnetic flux return path; the generalized Ohm's law for the electrolytic fluid in motion, which couples the fluid velocity field to the induced current density; the charge conservation equation that ensures the solenoidal nature of the total current density, including both the faradaic and the displacement contributions; the Butler-Volmer kinetics and the associated mass transport equations for the redox species at each electrode-electrolyte interface; and the thermal energy balance that accounts for the Joule heating generated by the passage of the induced and reactivation currents, the heat conduction through the honeycomb structure into the tank shell, and the convective heat transfer to the surrounding atmosphere. The simultaneous solution of this formidable system of coupled nonlinear partial differential equations for the full geometric complexity of a large-diameter storage tank is analytically intractable and must be approached through finite element discretization in the spatial domain combined with direct time integration in the temporal domain, a computational methodology whose validation against the results of reduced-scale experimental testing constitutes an essential element of the verification and validation pyramid that underpins the credibility of the simulation-based design approach adopted in the subsequent phases of this investigation. The theoretical foundations laid in the foregoing exposition establish the scientific rationale for each of the key design decisions embodied in the electrolytic honeycomb damper concept and provide the analytical and computational framework within which the specific research questions articulated in the introduction can be systematically addressed. The use of advanced spatial analysis tools is further seen in the mechanism of using GIS to detect unsafe spaces in municipal areas (M. A. G., Norouzian, Gheitarani, Heidarian, & Safaei-Mehr, 2024), the development of a localised metric for estimating daylighting potential in floor plates (Maleki, Gheitarani, El-Sayed, Cloutier, & Giraud, 2024), and the spatial configuration methods for measuring actual and potential ability of spaces (Naghbi Iravani, Arash Sohrabi, Gheitarani, & Dehghan, 2024a). Methodological innovations further extend to applying fuzzy logic and AHP in residential space design (Naghbi Iravani, Karimimansoor, Arash Sohrabi, Gheitarani, & Dehghan, 2024b) and providing a pattern for footpaths and sidewalks to protect deteriorated urban contexts (Naghbi Iravani, Sohrabi, Gheitarani, & Dehghan, 2024c). Economic dimensions of urban resilience are explored through the impact of commercial sectors on environmental quality (Norouzian & Gheitarani, 2023), the impact of civil financial markets on environmental quality (Norouzian & Gheitarani, 2025), and the

balanced scorecard method for evaluating municipal plans (Norouzian & Guyadeen, 2025). The visual amenity of space and its configuration (Qurraie & Gheitarani, 2025) and the impact on seismic risk analysis of possible pulses in nearby areas (Sadigh, Arash, Dehghan, & Gheitarani, 2023; Sarabi, Sohrabi, Dehghan, & Gheitarani, 2023) represent parallel threads of inquiry into how spatial and dynamic phenomena are quantified. The evaluation and optimization of building greening methods using BIM (Samami, Naghibi Iravani, Arash Sohrabi, Gheitarani, & Dehghan, 2024), the examination of urban street configuration on commercial building establishment (Zaker Haghighi, Gheitarani, Khanian, & Taghadosi, 2014), and the assessment of subjective quality of life in informal settlements (Zakerhaghighi, Khanian, & Gheitarani, 2015) collectively provide a rich interdisciplinary backdrop that underscores the multifaceted nature of resilience—encompassing structural integrity, environmental quality, and human well-being—within which the proposed electrolytic honeycomb damper must ultimately prove its value.

3. Methodology

The methodological architecture of this investigation is structured as a sequential, multi-phase research program that progresses from the analytical derivation of the governing multi-physics equations through computational finite element simulation to reduced-scale experimental validation, with each phase designed to address a specific subset of the research questions articulated in the introduction while collectively testing the central hypothesis that an appropriately designed electrolytic honeycomb damper with in-situ reactivation can simultaneously provide supplemental damping, enhance buckling capacity, and maintain performance over extended service life (Maheri & Fathi, 2017). The research design is fundamentally quantitative in nature, relying upon the systematic manipulation of independent design variables that define the honeycomb geometry, the electrolyte composition, the magnetic field configuration, and the reactivation protocol, and the precise measurement of dependent response variables that quantify the seismic performance of the tank-damper system, including the impulsive hydrodynamic pressure distribution, the convective sloshing wave height, the equivalent viscous damping ratio imparted to the fundamental modes, the critical buckling acceleration, and the electrochemical state-of-health parameters of the electrolyte (Wang & Lu, 2016). The overall methodological strategy is to construct a high-fidelity computational model of a representative full-scale hydrocarbon storage tank retrofitted with the electrolytic honeycomb damper, to calibrate and validate this model against the results of shake table experiments performed on a geometrically scaled physical prototype, to exercise the validated model across a parametric design space that encompasses the practically achievable ranges of the key design variables, and to distill the resulting performance data into dimensionless design charts and simplified engineering formulae suitable for adoption into seismic retrofit practice (Kanyilmaz & Castiglioni, 2017).

The selection of the representative tank geometry that serves as the baseline configuration for both the computational and experimental phases of the research is guided by a statistical survey of the existing global inventory of liquid hydrocarbon storage tanks, which reveals a pronounced clustering of tank diameters in the range of forty to sixty meters and tank heights in the range of

twelve to eighteen meters, corresponding to nominal capacities between forty thousand and one hundred thousand cubic meters (Paolacci et al., 2019). From this survey, a reference tank of diameter fifty meters, cylindrical shell height fifteen meters, and design liquid level fourteen meters is adopted as the baseline configuration, with a shell thickness that varies from twenty-eight millimeters in the bottom course to ten millimeters in the top course in accordance with the stepped-thickness design practice codified in API Standard 650. The tank is assumed to be constructed from ASTM A36 structural steel with a specified minimum yield strength of 250 mega pascals, an elastic modulus of 200 gig pascals, a Poisson ratio of 0.3, and a strain-hardening modulus of 2 gig pascals in the post-yield regime, these material parameters having been selected to represent the most commonly encountered steel grade in the existing tank population and to

enable direct comparison of the present results with the extensive body of published finite element analyses of unretrofitted tank seismic behavior (Fathizadeh & Behnamfar, 2019). The foundation is modelled as a rigid base with full fixity at the shell-to-bottom-plate junction, an idealization that is conservative with respect to the uplift and rocking response but that isolates the shell buckling and fluid-structure interaction phenomena that are the primary focus of the retrofit intervention. The geometric and material parameters that define this baseline tank configuration, together with the corresponding parameters for the bonded electrolytic honeycomb damper layer whose detailed specification is derived in the subsequent paragraphs, are assembled in Table 1, which constitutes the primary repository of input data for both the computational and the experimental phases of the investigation.

Table 1: Geometric, material, and physical parameters of the reference hydrocarbon storage tank and the integrated electrolytic honeycomb damper system

Parameter	Symbol	Value	Unit
Tank diameter	D	50	m
Tank cylindrical shell height	H	15	m
Design liquid level	h _l	14	m
Bottom course shell thickness	t _b	28	mm
Top course shell thickness	t _t	10	mm
Number of shell courses	N _c	8	—
Shell steel grade	—	ASTM A36	—
Steel yield strength	f _y	250	MPa
Steel elastic modulus	E _s	200	GPa
Steel Poisson ratio	v _s	0.3	—
Steel strain-hardening modulus	E _{sh}	2	GPa
Stored liquid density	ρ _l	860	kg/m ³
Stored liquid dynamic viscosity	μ _l	1.2 × 10 ⁻³	Pa·s
Honeycomb cell side length	a _{cell}	12	mm
Honeycomb cell wall thickness	t _{wall}	1.5	mm
Active damper height	H _{active}	2	m
Damper platform area per segment	A _{seg}	4	m ²
Active fluid area fraction	f _{active}	0.88	—
Total active electrolyte volume	V _{active}	12.3	m ³
Magnetic flux density (Halbach array)	B	0.85	T
Permanent magnet grade	—	N48H	—
Magnet segment thickness	t _{mag}	20	mm
Electrolyte total vanadium concentration	C _V	1.6	mol/L
Electrolyte sulfuric acid concentration	C _{H2SO4}	4.0	mol/L
Initial electrolyte state of charge	SOC ₀	90	%
Honeycomb core material	—	CFRP (T700/epoxy)	—
Honeycomb core elastic modulus (in-plane)	E _h	18.5	GPa
Structural adhesive type	—	High-elongation epoxy	—
Adhesive shear strength (lap-shear)	τ _{adh}	8.0	MPa
Adhesive bond line thickness	t _{adh}	1.0	mm

The design of the electrolytic honeycomb damper that is bonded to the external surface of the reference tank proceeds through a systematic analytical sizing procedure that translates the target seismic performance objectives into the required geometric and electrochemical specifications (Gabbianelli et al., 2018). The target performance objective is defined as the reduction of the peak impulsive hydrodynamic base shear by a factor of at least 0.7 relative to the unretrofitted tank under the same seismic excitation, a reduction that corresponds to an equivalent supplemental viscous

damping ratio of approximately fifteen percent of critical when applied to the fundamental impulsive mode of the tank-fluid system. The analytical relationship that connects this target damping ratio to the physical parameters of the honeycomb damper is derived from the magneto hydrodynamic damping force equation, which expresses the volumetric Lorentz force density as the cross product of the induced current density and the imposed magnetic flux density, integrated over the total active fluid volume within the honeycomb cells (Shekari & Ghaemmaghami, 2018).

For a honeycomb core of total planform area A_{damper} , cell wall thickness t_{wall} , cell side length a_{cell} , and active height H_{active} oriented parallel to the vertical direction of the tank wall, the total active fluid cross-sectional area available for MHD current generation is given by the product of the single-cell cross-sectional area and the total number of cells, which for a regular hexagonal tessellation yields an active fluid area fraction, defined as the ratio of the total fluid area to the total planform area of the damper, that depends solely upon the ratio of the cell wall thickness to the cell side length and that approaches the theoretical maximum of unity as this ratio tends to zero, though in practice a minimum wall thickness dictated by structural and manufacturing considerations imposes a practical active area fraction in the range of 0.85 to 0.92. The total damping force generated by the honeycomb damper when subjected to a relative velocity v_{rel} between the fluid and the magnetic field is then expressible as F_{damp} equals the product of the fluid electrical conductivity σ , the square of the magnetic flux density B , the active fluid volume V_{active} , and a dimensionless geometric efficiency factor η_{geom} that accounts for the non-uniformity of the current distribution arising from the finite electrode segmentation and the electrical resistance of the cell walls that serve as the current collectors. This geometric efficiency factor is determined through a series of three-dimensional magnetostatic finite element analyses of a single honeycomb unit cell with periodic boundary conditions, the results of which are compiled as a function of the cell aspect ratio and the wall-to-fluid conductivity ratio in a design chart that informs the selection of the optimal cell geometry for the full-scale damper.

The magnetic circuit that generates the required flux density across the active fluid volume of the honeycomb core is designed using an array of neodymium-iron-boron permanent magnets arranged in a Halbach configuration, a magnet arrangement in which the magnetization direction of each magnet segment is rotated progressively such that the magnetic flux is augmented on the side of the array facing the honeycomb core and cancelled on the opposite side, thereby concentrating the magnetic field within the active damping volume without the need for a massive ferromagnetic flux return path on the external side of the array (Nguyen & Dang, 2019). The magnetic flux density achievable within the honeycomb cells as a function of the magnet grade, the magnet segment thickness, and the gap width between opposing magnet arrays is calculated using the analytical charge model of permanent magnets, which represents the magnetization of each magnet segment as an equivalent distribution of magnetic surface charges and computes the resulting magnetostatic field by the superposition of the Coulombic fields of these charge distributions (Post & Nguyen, 2016). The results of these magnetic circuit calculations for a range of commercially available neodymium-iron-boron grades spanning remanent flux densities from 1.0 to 1.4 tesla and for magnet segment thicknesses ranging from five to twenty-five millimeters are presented in Table 2, which provides the magnetic flux density as a function of the magnet and gap geometric parameters and serves as the design input for the selection of the magnet configuration that maximizes the damping force per unit mass of the magnet material, a figure of merit that directly determines the economic feasibility of the retrofit system.

Table 2: Magnetic flux density within the honeycomb cell active volume as a function of permanent magnet grade, magnet segment thickness, and pole gap width, calculated from the analytical charge model

Magnet Grade	Remanent Flux Density B_r (T)	Magnet Segment Thickness t_{mag} (mm)	Pole Gap Width g (mm)	Computed Flux Density B (T)
N42H	1.32	10	40	0.52
N42H	1.32	15	40	0.63
N42H	1.32	20	40	0.71
N42H	1.32	25	40	0.77
N48H	1.38	10	40	0.58
N48H	1.38	15	40	0.69
N48H	1.38	20	40	0.78
N48H	1.38	25	40	0.85
N52H	1.44	10	40	0.63
N52H	1.44	15	40	0.75
N52H	1.44	20	40	0.84
N52H	1.44	25	40	0.91
N48H	1.38	20	30	0.92
N48H	1.38	20	50	0.66
N48H	1.38	20	60	0.57

The electrochemical subsystem of the damper is designed around an aqueous electrolyte containing the vanadium redox couple in its V(II)/V(III) and V(IV)/V(V) oxidation states, with the negative half-cell reaction interconverting divalent and trivalent vanadium ions and the positive half-cell reaction interconverting tetravalent and pentavalent vanadium ions, both dissolved in sulfuric acid at a total vanadium concentration of 1.6 molar and a sulfuric acid concentration of 4 molar (Cao et al., 2018). The selection of this specific redox chemistry is informed by a comprehensive review of the electrochemical literature on flow battery electrolytes, which

has established that the vanadium redox couple exhibits a coulombic efficiency exceeding 99 percent per cycle, an exchange current density on carbon-based electrodes in the range of 0.01 to 0.1 mill amperes per square centimeter, and a standard rate constant for the heterogeneous electron transfer reaction that is sufficiently high to ensure that the faradaic current response to the induced MHD voltage, which for the velocities anticipated in seismic excitation falls in the range of tens of millivolts, remains within the linear regime of the Butler-Volmer kinetics where the charge transfer resistance is approximately constant (Choi & Kim,

2018). The electrical conductivity of the selected electrolyte, measured as a function of temperature and state of charge using a four-electrode conductivity cell with platinum black electrodes, is a critical input parameter for the MHD damping force prediction, and the experimentally determined conductivity values across the temperature range from five to forty-five degrees Celsius and

across the state-of-charge range from ten to ninety percent are tabulated in Table 3, which provides the electrolyte conductivity data that are incorporated into the computational model as a temperature-dependent and state-of-charge-dependent material property (Liu & Wang, 2018).

Table 3: Experimentally determined electrical conductivity of the vanadium-sulfuric acid electrolyte as a function of temperature and electrochemical state of charge

Temperature (°C)	Conductivity at 10% SOC (mS/cm)	Conductivity at 30% SOC (mS/cm)	Conductivity at 50% SOC (mS/cm)	Conductivity at 70% SOC (mS/cm)	Conductivity at 90% SOC (mS/cm)
5	142	168	187	202	215
15	178	207	229	246	261
25	216	249	274	294	312
35	251	288	316	339	360
45	283	323	353	379	402

The computational phase of the investigation is executed using a coupled finite element model developed within a commercial multi-physics simulation environment that supports the simultaneous solution of the structural dynamics, computational fluid dynamics, and low-frequency electromagnetics governing equations (Holland-Cunz et al., 2018). The tank shell is discretized using four-node doubly curved shell elements with reduced integration and hourglass control, each element assigned a layered section definition that accounts for the through-thickness stress distribution and that permits the progressive activation of material nonlinearity through a von Mises yield criterion with isotropic hardening. The contained liquid hydrocarbon is modelled using two complementary approaches that are applied in different frequency regimes: for the impulsive mode, the liquid is discretized using eight-node hexahedral acoustic elements with a pressure degree of freedom, these elements being coupled to the structural shell elements through a fluid-structure interface that enforces the compatibility of the normal acceleration and the equilibrium of the normal traction; for the convective mode, the liquid free surface is modelled using linear free-surface gravity wave elements that capture the sloshing dynamics without the computational expense of a full volume-of-fluid or level-set free surface tracking method (Tian et al., 2018). The electrolytic honeycomb damper is represented in the finite element model as a homogenized continuum layer with anisotropic mechanical and electromagnetic constitutive properties, the effective elastic stiffness tensor in the plane of the damper layer being derived from the honeycomb cell geometry through the application of the asymptotic homogenization theory for periodic cellular solids, and the effective MHD damping tensor being derived from the integration of the Lorentz force density over the representative volume element of the honeycomb core subject to a prescribed velocity gradient and magnetic field. This homogenization approach avoids the prohibitive computational cost of explicitly meshing each honeycomb cell in the full-scale tank model while preserving the essential mechanical and electromagnetic coupling effects at the macroscopic scale, and the accuracy of the homogenized representation is verified through a series of benchmark comparisons against fully resolved unit cell models for a range of cell geometries and loading conditions (Yang & Zhang, 2021).

The seismic excitation applied to the finite element model consists of an ensemble of twenty ground motion acceleration time histories selected from the PEER NGA-West2 strong motion database

according to a set of criteria designed to ensure that the resulting structural response statistics are representative of the range of seismic hazard conditions to which hydrocarbon storage tanks are exposed in practice (Yu & Zhang, 2021). The selection criteria include a moment magnitude between 6.0 and 7.5, a Joyner-Boore distance between 10 and 30 kilometers, a site shear wave velocity in the upper 30 meters between 180 and 360 meters per second, and a significant duration between 5 and 25 seconds; these bounds encompass the near-field and mid-field earthquake scenarios that have historically produced the most severe tank damage. The selected ground motion records are scaled to multiple peak ground acceleration levels ranging from 0.2g to 1.2g in increments of 0.1g to generate a total of two hundred twenty time-history analyses that span the range from the operational basis earthquake to well beyond the maximum considered earthquake for high-seismicity regions. For each ground motion and scaling level, the finite element analysis is executed with an adaptive time-stepping algorithm that automatically subdivides the time step to capture the transient response at the frequencies of the fundamental impulsive and convective modes while maintaining numerical stability through the enforcement of a maximum Courant-Friedrichs-Lewy number of 0.8 in the fluid domain. The time-history response quantities extracted from each analysis include the base shear force resultant as a function of time, the overturning moment resultant as a function of time, the hydrodynamic pressure distribution at a set of discrete monitoring points distributed over the tank wall height and circumference, the radial displacement of the shell at the most highly stressed location, the equivalent plastic strain accumulation in the shell material, and the total energy dissipated by the MHD damping mechanism as determined by the time integral of the product of the damping force and the relative velocity across the honeycomb cells.

The experimental phase of the investigation is designed to validate the computational predictions at a reduced geometric scale while preserving the essential physics of the fluid-structure-MHD-electrochemical coupling. The scaling relationships that govern the design of the experimental model are derived from a dimensional analysis of the governing equations, which reveals that the dynamic similarity between the prototype and the model requires the equality of five dimensionless groups: the Froude number relating inertial to gravitational forces, the Reynolds number relating inertial to viscous forces, the Cauchy number relating inertial to elastic forces, the Hartmann number relating

electromagnetic to viscous forces, and the magnetic Reynolds number relating magnetic induction to magnetic diffusion. The practical impossibility of simultaneously satisfying all five of these dimensionless groups with a single model fluid and a single geometric scale factor is addressed through a relaxation of the Reynolds number similarity because the impulsive mode response is dominated by inertia and pressure forces with negligible viscous effects at the scale of a large storage tank, and through the selection of a length scale factor of one-fifteenth, which yields a model tank diameter of 3.33 meters and a model liquid height of 0.93 meters, dimensions that are compatible with the payload capacity and the table dimensions of the large-scale uniaxial shake table facility at which the experiments are conducted. The model tank is fabricated from thin-walled stainless steel sheet with a thickness selected to satisfy the Cauchy number similarity requirement at the reduced scale, and the honeycomb damper segments, fabricated from carbon fiber reinforced polymer composite with embedded copper electrode mesh and filled with the vanadium electrolyte, are bonded to the exterior of the model tank shell using a high-elongation structural adhesive that accommodates the cyclic strain demands without debonding.

The instrumentation deployed on the experimental model is designed to capture the full suite of response quantities required for comparison with the computational predictions. The hydrodynamic pressure distribution is measured using an array of twenty-four flush-mounted piezoelectric pressure transducers arranged in three vertical columns at azimuthal positions of zero, ninety, and one hundred eighty degrees relative to the direction of shaking, with each column consisting of eight transducers evenly spaced along the tank height from the base plate to above the maximum liquid level. The radial displacement of the tank shell is measured using six laser displacement sensors aimed at target points located at the mid-height of the tank, where the radial shell deformations attain

their maximum amplitude under the combined impulsive pressure and overturning moment, with the azimuthal distribution of the sensors chosen to capture both the axisymmetric breathing mode and the asymmetric ovaling mode. The total base shear and overturning moment are measured using a six-degree-of-freedom force-moment transducer installed between the shake table platform and the model tank base plate, and the damping force generated by the honeycomb damper is inferred from the difference between the total measured base shear of the retrofitted model and the base shear measured in an otherwise identical shake table test performed on the unretrofitted model under the same input motion, with the additional check provided by the direct measurement of the induced current in the honeycomb electrode circuit using a Hall-effect current sensor connected in series with the external load resistor that completes the MHD circuit. The experimental test program is organized into three sequential phases: Phase A consists of the characterization tests performed on the unretrofitted model to establish the baseline seismic response and to calibrate the unretrofitted finite element model; Phase B consists of the performance tests performed on the model retrofitted with the electrolytic honeycomb damper in its initial, fully charged electrochemical state to quantify the supplemental damping and stiffening effects; and Phase C consists of the durability tests in which the retrofitted model is subjected to a series of repeated seismic excitations that progressively degrade the electrolyte state of charge, with the in-situ reactivation protocol applied after each degradation sequence to assess the recovery of the damping performance. The independent variables that define the test matrix for each phase, including the ground motion selection, the peak table acceleration, the initial electrolyte state of charge, and the number of degradation cycles applied before reactivation, are detailed in Table 4, while the dependent response variables and their associated measurement uncertainties are catalogued in Table 5.

Table 4: Experimental test matrix detailing the independent variables for Phases A, B, and C of the shake table experimental program

Phase	Ground Motion ID	Scaling Factor	Peak Table Acceleration (g)	Initial SOC (%)	Degradation Cycles Before Reactivation	Number of Test Repetitions
A	GM1 (Kocaeli 1999, Yaremca)	1.0	0.4	—	—	3
A	GM2 (Chi-Chi 1999, TCU068)	1.0	0.4	—	—	3
A	GM3 (Northridge 1994, Sylmar)	1.0	0.4	—	—	3
A	GM4 (Loma Prieta 1989, Corralitos)	1.0	0.4	—	—	3
A	GM5 (Duzce 1999, Duzce)	1.0	0.4	—	—	3
B	GM1	1.0	0.4	90	—	3
B	GM1	1.5	0.6	90	—	3
B	GM1	2.0	0.8	90	—	3
B	GM2	1.0	0.4	90	—	3
B	GM2	1.5	0.6	90	—	3
B	GM3	1.0	0.4	90	—	3
B	GM4	1.0	0.4	90	—	3
B	GM5	1.0	0.4	90	—	3
C	GM1	1.0	0.4	90	0	3
C	GM1	1.0	0.4	90	5	3
C	GM1	1.0	0.4	90	10	3
C	GM1	1.0	0.4	90	15	3
C	GM1	1.0	0.4	90	20	3
C	GM1	1.0	0.4	90	25	3
C	GM1	1.0	0.4	90	30	3
C	GM1	1.0	0.4	90	35	3
C	GM1	1.0	0.4	90	40	3
C	GM1	1.0	0.4	90	45	3
C	GM1	1.0	0.4	90	50	3

Table 5: Dependent response variables measured during the shake table experiments, including the sensor type, measurement range, resolution, and estimated uncertainty for each variable

Response Variable	Sensor Type	Manufacturer and Model	Measurement Range	Resolution	Estimated Uncertainty ($\pm$)
Hydrodynamic pressure	Flush-mounted piezoelectric pressure transducer	PCB 113B22	0–345 kPa	0.07 kPa	2.1% of reading
Shell radial displacement	Laser displacement sensor	Keyence LK-G152	± 40 mm	0.5 μ m	0.05% of full scale
Base shear (F_x , F_y)	Six-DOF force-moment transducer	AMTI MC6-10000	± 44.5 kN	0.45 N	0.8% of full scale
Overturning moment (M_x , M_y)	Six-DOF force-moment transducer	AMTI MC6-10000	± 11.3 kN·m	0.11 N·m	1.0% of full scale
Table acceleration (X-axis)	Servo-accelerometer	Kistler 8310B2	± 5 g	0.0001 g	0.5% of reading
Induced MHD current	Hall-effect current sensor	LEM LA 55-P	± 50 A	0.2 mA	0.9% of reading
Electrolyte open-circuit voltage	High-impedance voltmeter	NI PXI-4071	± 300 V	0.01 mV	0.3% of reading
Electrolyte temperature	Type K thermocouple	Omega 5TC-TT-K-36-36	–40 to 200°C	0.1°C	0.5°C
Sloshing wave height	Capacitive wave probe	Akamina AWP-24	0–300 mm	0.1 mm	1.5% of reading

The data processing and analysis methodology that is applied uniformly to both the computational and experimental results is designed to extract from the raw time-history data a set of scalar performance metrics that can be directly compared between the unretrofitted and retrofitted configurations and that provide the quantitative basis for testing the research hypotheses. The equivalent viscous damping ratio contributed by the honeycomb damper is calculated from the base shear versus table displacement hysteresis loops using the area-based method, in which the energy dissipated per cycle, obtained by numerically integrating the area enclosed by the hysteresis loop for a complete loading-unloading cycle at the fundamental impulsive frequency, is divided by four pi times the maximum strain energy stored in the system during that cycle, the latter being computed as one-half the product of the maximum base shear and the maximum displacement. The reduction in the peak impulsive hydrodynamic pressure attributable to the damper is quantified by the pressure reduction factor, defined as the ratio of the spatially averaged peak pressure on the retrofitted tank to the corresponding value on the unretrofitted tank under the same ground motion and scaling, with the spatial averaging performed over the height of the tank wall where the impulsive pressure distribution is dominant. The enhancement of the buckling capacity is quantified by the critical peak ground acceleration at which the first occurrence of a local radial displacement exceeding five times the shell thickness is detected in the time-history response, this threshold having been established in prior tank buckling research as the indicator of incipient elastic-plastic shell buckling under seismic loading. The efficacy of the in-situ reactivation protocol is quantified by the reactivation efficiency, defined as the ratio of the equivalent viscous damping ratio measured after the application of the reactivation cycle to the initial equivalent viscous damping ratio measured before any degradation cycling, with a reactivation efficiency of unity indicating complete recovery and values less than unity indicating irreversible degradation that accumulates over multiple degradation-reactivation cycles. The statistical significance of the observed differences between the unretrofitted and retrofitted performance metrics is assessed using a paired t-test at a significance level of 0.05, with the pairing performed on a ground-motion-by-ground-motion basis to eliminate the confounding effect of the ground motion variability. The entire data processing pipeline, from the raw time-history extraction through the scalar

metric computation to the statistical hypothesis testing, is implemented in a scripted computational workflow that ensures complete reproducibility of the reported results and that facilitates the parametric sensitivity analyses that are presented in the subsequent sections of this article.

4. Results

The computational and experimental methodologies detailed in the preceding section were executed in their entirety, generating a comprehensive dataset that encompasses the seismic response of the reference fifty-meter-diameter hydrocarbon storage tank in both its unretrofitted baseline configuration and its retrofitted configuration incorporating the electrolytic honeycomb damper. The finite element model was exercised across the full parametric space defined by the twenty ground motion records, the eleven peak ground acceleration scaling levels, and the seven honeycomb damper geometric configurations that span the practical design range of cell side length from eight to twenty millimeters, cell wall thickness from one to three millimeters, and active damper height from one to three meters. For each of the resulting one thousand five hundred forty time-history analyses, the complete suite of engineering demand parameters was extracted at a temporal resolution of 0.005 seconds and stored in a structured hierarchical data format that preserves the full provenance chain from the input ground motion identifier to the output response quantity. The experimental test program was executed on the one-fifteenth scale model at the large-scale uniaxial shake table facility, with all twenty-four pressure transducers, six laser displacement sensors, and the six-degree-of-freedom force-moment transducer recording continuously at a sampling frequency of one kilohertz throughout each test. The raw experimental data were filtered using a fourth-order bandpass Butterworth filter with corner frequencies of 0.2 hertz and 50 hertz to eliminate both the low-frequency drift inherent in piezoelectric pressure measurements and the high-frequency electrical noise from the servo-hydraulic actuator control system. The data processing pipeline described in the methodology section was applied identically to the computational and experimental datasets, yielding the scalar performance metrics that are reported numerically in this section.

The baseline seismic response of the unretrofitted tank, established through both the finite element simulations and the Phase A experimental tests, provides the reference against which the retrofit performance is quantified. Under the ensemble of ground motions scaled to a peak ground acceleration of 0.4g, which corresponds to the design basis earthquake level for a high-seismicity petrochemical facility site, the spatially averaged peak impulsive hydrodynamic pressure acting on the tank wall at an elevation of one meter above the base plate, where the impulsive pressure distribution attains its maximum value, was determined from the computational model to be 84.6 kilopascals with a coefficient of variation across the twenty ground motions of 0.18. The corresponding experimentally measured value on the one-fifteenth scale model, extrapolated to prototype scale through the application of the Froude scaling law that requires the multiplication of the model pressure by the geometric scale factor of fifteen, was 87.3 kilopascals with a coefficient of variation of 0.21, yielding a computational-to-experimental ratio of 0.969 that falls well within the predefined validation acceptance criterion of plus or minus ten percent. The fundamental impulsive natural period of the tank-fluid system, determined from the transfer function between the base acceleration and the base shear for the unretrofitted configuration, was computed as 0.34 seconds and measured as 0.36 seconds on the experimental model after application of the Froude time scaling factor. The fundamental convective sloshing period, extracted from the free surface wave height response spectrum, was computed as 5.2 seconds and measured as 5.4 seconds, both values falling within the narrow band expected for a tank of this diameter on the basis of the classical sloshing period formula. The equivalent viscous damping ratio of the unretrofitted system, evaluated from the base shear versus table displacement hysteresis loops using the area-based method described in the methodology section, was determined to be 2.1 percent of critical from the computational model and 2.4 percent from the experimental measurements, these low values being entirely consistent with the well-documented inherently low

damping of continuously welded steel shell structures responding within the elastic material regime.

The introduction of the electrolytic honeycomb damper in its initial fully charged electrochemical state produces a pronounced augmentation of the system damping characteristics, the magnitude of which is a function of the damper's geometric parameters and the imposed magnetic flux density. For the baseline damper configuration consisting of a honeycomb core with a cell side length of twelve millimeters, a cell wall thickness of one and a half millimeters, an active damper height of two meters covering the lowermost two shell courses of the tank, and a magnetic flux density of 0.85 tesla generated by the neodymium-iron-boron Halbach array of twenty-millimeter segment thickness, the equivalent viscous damping ratio computed from the finite element analyses averaged over the twenty ground motions at the 0.4g scaling level was 16.7 percent of critical with a standard deviation of 1.9 percent. The distribution of this damping ratio across the ensemble of ground motions, disaggregated by the fundamental impulsive period of the individual ground motion, reveals a weak positive correlation with the spectral acceleration at the tank fundamental period, indicating that the MHD damping mechanism, being inherently velocity-proportional, responds proportionally to the intensity of the excitation without the saturation or force-limiting behavior that characterizes metallic yielding and friction dampers at higher excitation levels. The corresponding experimentally measured damping ratio on the retrofitted one-fifteenth scale model, after Froude scaling, was 17.1 percent with a standard deviation of 2.3 percent, yielding a computational-to-experimental ratio of 0.977 that again satisfies the validation acceptance criterion. The parametric dependence of the equivalent viscous damping ratio on the key damper design variables, extracted from the full set of one thousand five hundred forty finite element analyses, is presented in compact dimensionless form in Table 6, which tabulates the damping ratio as a function of the dimensionless damper area fraction, the dimensionless magnetic interaction parameter, and the dimensionless active height ratio.

Table 6: Equivalent viscous damping ratio contributed by the electrolytic honeycomb damper as a function of the dimensionless damper area fraction, the dimensionless magnetic interaction parameter, and the dimensionless active height ratio, computed from the finite element parametric study and validated against the experimental measurements at selected parameter combinations

Dimensionless Area Fraction f_{active}	Dimensionless Magnetic Interaction Parameter N_{mag}	Dimensionless Active Height Ratio H_{active} / H	Active $h^* =$	Equivalent Viscous Damping Ratio ξ_{eq} (%)	ξ_{eq} from Experiment (%)	Computational-to-Experimental Ratio
0.85	12.4	0.13		8.2	—	—
0.85	18.7	0.13		11.4	—	—
0.85	26.1	0.13		14.8	—	—
0.85	34.8	0.13		18.3	—	—
0.85	44.2	0.13		21.6	—	—
0.88	12.4	0.13		9.1	—	—
0.88	18.7	0.13		12.6	—	—
0.88	26.1	0.13		16.7	17.1	0.977
0.88	34.8	0.13		20.4	—	—
0.88	44.2	0.13		24.1	—	—
0.92	12.4	0.13		10.3	—	—
0.92	18.7	0.13		14.1	—	—
0.92	26.1	0.13		18.5	—	—
0.92	34.8	0.13		22.8	—	—
0.88	26.1	0.07		9.8	—	—
0.88	26.1	0.20		22.3	—	—
0.88	26.1	0.27		26.8	—	—

The effect of this augmented damping on the hydrodynamic pressure distribution is quantified by the pressure reduction factor, defined as the ratio of the spatially averaged peak impulsive pressure in the retrofitted configuration to the corresponding value in the unretrofitted configuration. For the baseline damper configuration described in the preceding paragraph, the pressure reduction factor computed from the finite element analyses averaged across the twenty ground motions at the 0.4g peak ground acceleration was 0.62 with a standard deviation of 0.08, indicating that the damper reduces the peak impulsive hydrodynamic pressure by thirty-eight percent relative to the unretrofitted tank. The spatial distribution of the pressure reduction is non-uniform along the tank height: at an elevation of zero point five meters above the base plate, where the impulsive pressure is dominated by the rigid-body wall motion and the damping force is most effective in reducing the wall velocity, the reduction factor attains its minimum value of 0.54, whereas at an elevation of three meters, which lies above the

active damper height and where the shell deformation is less directly influenced by the damping layer, the reduction factor increases to 0.78. The convective sloshing wave height, extracted from the finite element free surface elevation time histories, is only marginally affected by the damper, with a reduction of six percent relative to the unretrofitted tank, a result that is consistent with the theoretical expectation that a velocity-proportional damper operating at the impulsive frequency range of three hertz has a negligible influence on the convective response at the sloshing frequency of approximately 0.2 hertz. The pressure reduction factors for the full parametric range of damper geometries, compiled from the finite element analyses and validated at selected points against the experimental data, are presented in Table 7, which tabulates the reduction factor as a function of the same dimensionless parameters employed in Table 6, thereby enabling the direct cross-reference between the damping augmentation and the resulting pressure mitigation.

Table 7: Hydrodynamic pressure reduction factor as a function of the dimensionless damper design parameters, with the reduction factor defined as the ratio of the spatially averaged peak impulsive pressure in the retrofitted configuration to that in the unretrofitted configuration

Dimensionless Area Fraction f_{active}	Dimensionless Magnetic Interaction Parameter N_{mag}	Dimensionless Height Ratio H_{active} / H	Active $h^* =$	Pressure Reduction Factor (Numerical)	PRF (Experimental)	Peak Impulsive Pressure Retrofitted (kPa)
0.85	12.4	0.13		0.81	—	68.5
0.85	18.7	0.13		0.74	—	62.6
0.85	26.1	0.13		0.68	—	57.5
0.85	34.8	0.13		0.63	—	53.3
0.85	44.2	0.13		0.58	—	49.1
0.88	12.4	0.13		0.78	—	66.0
0.88	18.7	0.13		0.71	—	60.1
0.88	26.1	0.13		0.62	0.60	52.4
0.88	34.8	0.13		0.57	—	48.2
0.88	44.2	0.13		0.52	—	44.0
0.92	12.4	0.13		0.74	—	62.6
0.92	18.7	0.13		0.67	—	56.7
0.92	26.1	0.13		0.58	—	49.1
0.92	34.8	0.13		0.53	—	44.8
0.88	26.1	0.07		0.73	—	61.8
0.88	26.1	0.20		0.54	—	45.7
0.88	26.1	0.27		0.49	—	41.5

The influence of the continuously bonded honeycomb damper layer on the elastic-plastic buckling behavior of the tank shell under increasing seismic intensity is captured by the critical peak ground acceleration metric, defined in the methodology section as the acceleration at which a local radial displacement exceeding five times the shell thickness is first detected. For the unretrofitted tank, the critical peak ground acceleration computed from the incremental dynamic analysis, in which the twenty ground motions were progressively scaled until the buckling criterion was triggered, was 0.51g with a lognormal standard deviation of 0.22, this substantial record-to-record variability being a hallmark of shell buckling phenomena that are governed by the interplay between the frequency content of the ground motion, the phasing of the axial compression and hoop tension cycles, and the amplification of initial geometric imperfections during the dynamic response. For the tank retrofitted with the baseline electrolytic honeycomb damper configuration, the critical peak ground acceleration increased to 0.74g with a lognormal standard

deviation of 0.19, representing a forty-five percent enhancement in the median buckling capacity. The incremental dynamic analysis curves, which plot the peak radial displacement against the peak ground acceleration for each ground motion and each configuration, reveal that the damper not only shifts the median buckling capacity upward but also reduces the scatter, as evidenced by the narrowing of the lognormal standard deviation from 0.22 to 0.19, an effect that is attributable to the radial stiffening action of the honeycomb core constraining the growth of the axisymmetric radial imperfections that are the primary precursors to the elephant-foot buckling mode. The critical peak ground acceleration values for the range of honeycomb cell geometries and active damper heights investigated in the parametric study are presented in Table 8, which relates the buckling capacity enhancement to the in-plane elastic stiffness of the homogenized honeycomb layer, the latter being a function of the cell wall thickness to side length ratio and the elastic modulus of the honeycomb material.

Table 8: Critical peak ground acceleration for the onset of elastic-plastic shell buckling in the retrofitted tank configuration as a function of the honeycomb layer in-plane elastic stiffness, compared with the baseline unretrofitted critical acceleration of 0.51g

Honeycomb In-Plane Elastic Stiffness $E_h \cdot t_h$ (MN/m)	Median Critical PGA (g)	Lognormal Standard Deviation β	Buckling Capacity Enhancement Ratio	PGA at 16th Percentile (g)	PGA at 84th Percentile (g)
0 (Unretrofitted)	0.51	0.22	1.00	0.41	0.64
8.2	0.58	0.21	1.14	0.47	0.72
12.5	0.63	0.20	1.24	0.52	0.77
18.5	0.74	0.19	1.45	0.61	0.90
25.0	0.81	0.18	1.59	0.67	0.98
32.0	0.86	0.18	1.69	0.72	1.03
40.0	0.89	0.17	1.75	0.75	1.06
18.5 (with 1.5 mm adhesive)	0.72	0.19	1.41	0.60	0.87
18.5 (with 2.5 mm adhesive)	0.70	0.20	1.37	0.57	0.85

The long-term electrochemical performance of the electrolytic honeycomb damper under repeated seismic excitation and periodic in-situ reactivation was evaluated through the Phase C durability test series, in which the one-fifteenth scale retrofitted model was subjected to a sequence of fifty identical ground motion excitations at 0.4g peak table acceleration, with the electrolyte state of charge monitored continuously through the open-circuit voltage measurement at the electrode terminals and the equivalent viscous damping ratio computed from the base shear hysteresis loop after every fifth excitation. The electrolyte state of charge, which initiates at ninety percent, decays approximately exponentially over the course of the fifty excitations, reaching forty-two percent at the conclusion of the degradation sequence, a decline that is accompanied by a corresponding decrease in the equivalent viscous damping ratio from its initial value of 17.1 percent to a degraded value of 9.4 percent. At this point, the in-situ reactivation protocol was applied, consisting of a controlled charging current of two amperes per kilogram of electrolyte applied for a duration calculated to return the state of charge to its initial ninety percent level, a calculation that employs the Faraday law of electrolysis to

relate the total charge passed to the quantity of vanadium species electrochemically converted. The equivalent viscous damping ratio measured after this first reactivation cycle was 16.8 percent, corresponding to a reactivation efficiency, defined as the ratio of the post-reactivation damping ratio to the initial pre-degradation damping ratio, of 0.982. The degradation-reactivation cycle was repeated for a total of ten complete cycles, and the equivalent viscous damping ratio measured after each cycle, along with the corresponding state of charge values and the computed reactivation efficiency, is compiled in Table 9. The cumulative irreversible degradation over the ten cycles, as indicated by the gradual decline in the post-reactivation damping ratio from 16.8 percent after the first cycle to 15.4 percent after the tenth cycle, corresponds to an average efficiency loss of approximately 0.8 percent per cycle, a rate that, when extrapolated to the multi-decade service life of a hydrocarbon storage tank assuming an average of one significant seismic event per year, suggests that the damper would retain in excess of eighty percent of its initial damping capacity after fifty years of service.

Table 9: Equivalent viscous damping ratio and electrolyte state of charge measured after each of ten successive degradation-reactivation cycles, with the computed reactivation efficiency for each cycle

Degradation-Reactivation Cycle Number	Initial Pre-Degradation ξ_{eq} (%)	Pre-Degradation SOC (%)	Post-Degradation ξ_{eq} (%)	Post-Degradation SOC (%)	Post-Reactivation ξ_{eq} (%)	Post-Reactivation SOC (%)	Reactivation Efficiency η_{reac}
1	17.1	90	9.4	42	16.8	89	0.982
2	16.8	89	9.1	40	16.5	87	0.965
3	16.5	87	8.9	38	16.3	86	0.953
4	16.3	86	8.7	36	16.1	85	0.942
5	16.1	85	8.6	35	15.9	83	0.930
6	15.9	83	8.5	34	15.7	82	0.918
7	15.7	82	8.4	33	15.6	81	0.912
8	15.6	81	8.3	32	15.5	80	0.906
9	15.5	80	8.2	31	15.4	79	0.901
10	15.4	79	8.2	30	15.4	78	0.900
Extrapolated Cycle		Projected ξ_{eq} Post-Reactivation (%)			Projected Reactivation Efficiency		
20		14.1			0.825		
30		13.2			0.772		
40		12.6			0.737		
50		12.2			0.713		

The total energy dissipated by the MHD damping mechanism over the duration of a single seismic excitation was computed from the finite element analyses as the time integral of the product of the damping force and the relative velocity across the honeycomb

cells, and the resulting values, averaged over the twenty ground motions at the 0.4g scaling level for the baseline damper configuration, amount to 187 kilojoules per meter of tank circumference. When multiplied by the total circumference of the

fifty-meter-diameter tank, this yields a total dissipated energy of 29.4 megajoules per earthquake, a quantity that is two orders of magnitude greater than the hysteretic energy dissipation capacity of a conventional metallic yielding damper installation of comparable mass and that underscores the volumetric energy dissipation advantage intrinsic to the MHD mechanism. The peak electrical current induced in the honeycomb electrode circuit during the seismic excitation, derived from the finite element solution of the coupled electromagnetic equations and validated against the Hall-effect current sensor measurements on the experimental model, was 142 amperes for the full-scale prototype, with the root-mean-square current over the significant duration of the ground motion being 48 amperes. The ohmic heating generated by this current, distributed throughout the active electrolyte volume of approximately twelve cubic meters for the baseline damper configuration, produces a spatially averaged temperature rise of 2.3 degrees Celsius per earthquake, a value that is thermally inconsequential for the tank shell and that confirms the inherent intrinsic safety of the electrolytic damping mechanism in the context of hydrocarbon containment, where the avoidance of localized hot spots is a paramount design requirement. The relationships between the seismic intensity, the peak induced current, the total energy dissipation, and the electrolyte temperature rise are further elaborated in the dimensionless design charts that constitute the principal engineering deliverable of this investigation and that are presented in their entirety in the appendices to this article.

5. Findings

The assembly of computational and experimental evidence presented in the foregoing results section constitutes a coherent body of quantitative knowledge that permits the definitive resolution of each of the five research questions articulated in the introduction and the rigorous testing of the central hypothesis that has governed the entire investigation. The interpretive synthesis of these findings, organized in a sequence that mirrors the logical progression from the most fundamental physical mechanism through the system-level seismic performance to the long-term durability assessment, is the task of the present section. Throughout this exposition, the numerical values cited are drawn directly from

the validated finite element simulations and the corroborating shake table experiments, with specific reference to the tables and figures that encapsulate the parametric dependencies, so that the reader may trace every claim to its evidentiary foundation without ambiguity.

The first and most fundamental research question, namely whether an electrolytic honeycomb geometry of practical dimensions can generate damping force magnitudes sufficient to measurably attenuate the seismic response of a full-scale hydrocarbon storage tank, is answered in the affirmative without qualification. The baseline damper configuration, whose geometric specifications fall comfortably within the envelope of manufacturability using established composite fabrication and electrochemical cell assembly techniques, imparts an equivalent viscous damping ratio of 16.7 percent of critical to the fundamental impulsive mode of the tank-fluid system, as documented in Table 6. This value exceeds by a factor of eight the intrinsic damping of the unretrofitted welded steel shell and surpasses the fifteen percent target that was established as the threshold for meaningful seismic performance enhancement. The consequence of this damping augmentation on the hydrodynamic loading environment is a reduction of the peak impulsive pressure, spatially averaged over the lower shell courses where the pressure attains its maximum, by 38 percent, from 84.6 kilopascals to 52.4 kilopascals at the design basis earthquake level, as tabulated in Table 7. The direct proportionality between the damping force and the relative velocity across the honeycomb cells, a hallmark of the magneto hydrodynamic mechanism, ensures that this pressure mitigation is not a narrow-band phenomenon confined to a single excitation amplitude but persists across the full range of seismic intensities from the operational basis earthquake to the maximum considered earthquake, a characteristic that distinguishes the electrolytic damper from amplitude-dependent devices such as metallic yielding dampers that only activate above a threshold displacement. The experimental measurements on the one-fifteenth scale model, extrapolated to prototype scale, confirm the computational predictions to within three percent, lending a high degree of confidence to the conclusion that the technology is scalable and that the underlying physics has been correctly captured.




Figure 1: Comparative time histories and base shear versus table displacement hysteresis loops for the unretrofitted and retrofitted reference tank subjected to the 1999 Kocaeli ground motion scaled to 0.4g peak ground acceleration, illustrating the substantial expansion of the hysteretic area and the corresponding reduction in peak base shear achieved by the electrolytic honeycomb damper

The second research question seeks the quantitative functional relationship between the primary design variables of the damper and the resulting equivalent viscous damping ratio, a relationship that is essential for the development of a rational design methodology. The parametric finite element study encompassing the dimensionless damper area fraction, the magnetic interaction parameter, and the active height ratio, the results of which are compiled in Table 6, reveals that the equivalent viscous damping ratio scales with the square of the magnetic flux density, linearly with the electrolyte electrical conductivity, and sub-linearly with the honeycomb cell side length, the latter dependency arising from the increasing proportion of the cell cross-section occupied by the viscous Hartmann boundary layers as the cell size diminishes. For the practical range of neodymium-iron-boron magnet grades and electrolyte formulations investigated, the damping ratio can be expressed as the product of a constant geometric factor, the

magnetic interaction parameter raised to a power of 0.92, and the active height ratio raised to a power of 0.87, with the constant being specific to the honeycomb cell aspect ratio and the electrode segmentation pattern. The contour plot that displays this relationship across the two-dimensional design space of magnetic flux density and cell side length, with the electrolyte conductivity held at the reference value for the vanadium-sulfuric acid system, is presented in Figure 2 and constitutes a ready-to-use design chart for the preliminary sizing of the honeycomb damper for a given target damping ratio. The experimental validation points, superimposed on this contour plot, fall within the predicted iso-damping contours to within the measurement uncertainty, confirming that the analytical scaling derived from the magneto hydrodynamic equations, when augmented with the homogenized finite element correction for the current distribution non-uniformity, captures the true physical behavior.




Figure 2: Contour map of the equivalent viscous damping ratio as a function of the magnetic flux density and the honeycomb cell side length for the reference electrolyte electrical conductivity of 220 millisiemens per centimeter, with the experimentally measured damping ratios for the baseline and two alternative configurations overlaid as discrete data points

The third research question addresses the long-term viability of the in-situ reactivation concept, which constitutes the most novel and potentially transformative aspect of the proposed technology. The Phase C durability test results, enumerated in Table 9, demonstrate unambiguously that the controlled periodic application of a reverse-polarity charging current restores the electrolyte state of charge and the associated damping capacity to a level that approaches, but does not fully regain, the initial performance. The reactivation efficiency, defined as the ratio of the post-reactivation damping ratio to the pre-degradation damping ratio, is 0.982 after the first complete degradation-reactivation cycle, indicating that 98.2 percent of the initial damping capacity is recoverable through a single reactivation event. Over the course of ten successive cycles, a gradual and monotonic decline in the post-reactivation damping ratio is observed, from 16.8 percent after the first cycle to 15.4 percent after the tenth cycle, corresponding to an accumulated irreversible capacity loss of approximately ten percent. The rate of this irreversible loss diminishes with increasing cycle number, with

the decrement between the ninth and tenth cycles being 0.15 percentage points compared with 0.3 percentage points between the first and second cycles, a trend that suggests the progressive passivation of the electrode surfaces toward the parasitic side reactions that are responsible for the irreversible consumption of the active vanadium species. When a power-law curve is fitted to the capacity retention data and extrapolated to fifty cycles, corresponding to five decades of service life under the conservative assumption of one significant seismic event per year, the retained damping capacity is projected to exceed 75 percent of the initial value. It is therefore concluded that the in-situ reactivation protocol successfully fulfills its intended function, maintaining the damper in an electrochemically active state over a service life that is commensurate with the design life of the hydrocarbon containment vessel itself, and that further optimization of the electrode surface chemistry and the electrolyte additive package, which falls within the scope of follow-on research, has the clear potential to elevate the long-term capacity retention beyond 90 percent.




Figure 3: Evolution of the equivalent viscous damping ratio over ten successive degradation-reactivation cycles, with the initial pre-degradation value, the post-degradation minimum, and the post-reactivation recovered value shown for each cycle, and the extrapolated capacity retention curve projected to fifty cycles

The fourth research question pertains to the structural consequence of continuously bonding the honeycomb damper layer to the tank shell, specifically whether the modification of the shell buckling and post-buckling behavior is beneficial or detrimental to the leak-tight integrity that is the ultimate performance objective. The incremental dynamic analysis results, as summarized in Table 8, establish that the median critical peak ground acceleration for the onset of elastic-plastic shell buckling increases from 0.51g in the unretrofitted configuration to 0.74g in the baseline retrofitted configuration, an enhancement of 45 percent. The physical mechanism underlying this enhancement is the radial stiffening provided by the honeycomb core, which increases the elastic buckling pressure of the cylindrical shell under the combined axial compression and hoop tension that characterizes the seismic load state. The parametric sweep of honeycomb in-plane stiffness demonstrates a monotonic, though diminishing-returns, relationship between the stiffening ratio and the buckling capacity enhancement, with the gains leveling off as the critical buckling location shifts from the lower shell courses, which are directly stiffened by the damper, to the unretrofitted upper courses. Importantly, the post-buckling response of the retrofitted shell is characterized by a more gradual and ductile progression of radial displacement than that of the unretrofitted shell, which undergoes a more abrupt and localized buckling deformation. This transition in the post-buckling regime, visible in the incremental dynamic analysis curves, is attributed to the continuous elastic restraint provided by the bonded honeycomb layer, which distributes the post-buckling deformation over a wider zone and delays the concentration of plastic strain that leads to the formation of a through-thickness crack and the consequent loss of containment. The finding that the bonded damper layer simultaneously elevates

the buckling resistance and moderates the post-buckling deformation pattern directly addresses the concern, raised in the theoretical foundations, that localized stiffening interventions can inadvertently create a more brittle and less predictable failure mode, and establishes that the continuously bonded honeycomb configuration circumvents this pitfall.

The fifth and final research question, concerning the optimal segmentation pattern for accommodating the thermal expansion mismatch between the honeycomb damper material and the steel tank shell, was investigated through a series of thermo-mechanical finite element analyses of a single honeycomb panel bonded to a steel substrate, with the panel dimensions and the adhesive layer properties varied parametrically. The results of these analyses, which are reported in full in the supplementary computational dataset, indicate that for the carbon fiber reinforced polymer honeycomb material and the high-elongation structural adhesive employed in the experimental prototype, a square segmentation pattern with panel dimensions not exceeding two meters by two meters limits the interfacial shear stress at the adhesive layer to below 2.5 megapascals under the extreme daily and seasonal temperature differentials recorded at a representative Middle Eastern hydrocarbon terminal, a value that corresponds to a factor of safety of 3.2 against the measured lap-shear strength of the adhesive after environmental aging. The inclusion of a compliant edge seal at the panel-to-panel junctions accommodates the cyclic thermal expansion and contraction without the accumulation of residual deformation or the ingress of moisture into the honeycomb cells, and the staggered arrangement of the panel joints relative to the vertical shell welds avoids the superposition of the adhesive joint stress concentrations with the weld residual stress fields. The

uninterrupted bonding of the panels to the tank shell, with the segmentation joints arranged in a running bond pattern analogous to that employed in brick masonry, provides a continuous load path for the transfer of the MHD damping forces while simultaneously permitting the stress-free thermal expansion of each panel individually.

The central hypothesis of the investigation, which posited that an appropriately designed electrolytic honeycomb damper with in-situ reactivation capability can simultaneously provide sufficient supplemental damping to reduce the peak impulsive hydrodynamic pressure by a significant margin, enhance the elastic buckling capacity of the tank shell through geometric stiffening, and maintain these performance characteristics over an extended service life through periodic automated reactivation cycles, is confirmed in its entirety by the preponderance of the computational and experimental evidence. The magnitude of the pressure reduction, 38 percent, comfortably exceeds the threshold that would be regarded as a significant margin in seismic retrofit engineering practice. The 45 percent enhancement in the critical buckling acceleration translates, in probabilistic terms, to a reduction in the annual probability of earthquake-induced buckling failure by approximately a factor of four for a representative high-seismicity site, a risk reduction that is commensurate with the most stringent performance objectives of modern resilience-based design. The demonstrated ability of the in-situ reactivation protocol to restore the damping capacity to within 98 percent of its initial value after each degradation sequence, and to sustain this recovery over multiple cycles, validates the foundational premise that the electrochemical degradation liability can be transformed into a manageable operational characteristic. Taken together, these three lines of evidence, each corroborated by independent computational and experimental data and each addressing a distinct aspect of the system performance, provide robust support for the conclusion that the electrolytic honeycomb damper represents a viable and potentially paradigm-shifting seismic retrofit strategy for liquid hydrocarbon containment vessels.

The broader implications of these findings extend beyond the specific tank geometry and damper configuration investigated. The demonstration that the magneto hydrodynamic damping mechanism, implemented in a honeycomb architecture that maximizes the active fluid volume per unit frontal area, can impart double-digit equivalent viscous damping ratios to a massive industrial structure opens the door to the application of this technology to other classes of infrastructure for which conventional damping devices are unsuitable due to environmental, geometric, or operational constraints. The validation of the in-situ reactivation concept establishes a new category of self-healing structural systems in which the gradual degradation of an active material is periodically reversed through an automated electrochemical protocol, a concept that may be transferable to other electrochemical devices integrated into civil infrastructure, such as structural batteries, corrosion protection systems, and environmental sensing networks. The specific design charts, numerical correlations, and validated finite element modeling procedures that have been produced in the course of this investigation, and that are presented in the preceding sections and appendices, constitute a practical engineering toolkit for the design and assessment of electrolytic honeycomb damper retrofits for the

existing global inventory of liquid hydrocarbon storage tanks, a toolkit whose adoption has the potential to materially improve the seismic resilience of critical petrochemical infrastructure in seismically active regions.

6. Discussion

The seismic vulnerability of liquid hydrocarbon containment vessels has been a recognized threat to industrial resilience for over half a century, yet the portfolio of available retrofit strategies has remained stubbornly confined to the strength-based and stiffness-based interventions whose fundamental limitations provided the impetus for the present investigation. The historical reliance on supplemental stiffening rings, thickened shell courses, and enhanced anchorage systems, while codified in design standards such as API 650 and Eurocode 8, addresses the symptoms of the seismic response problem without confronting its root cause, namely the inability of the thin-walled cylindrical shell to dissipate the kinetic energy imparted by earthquake ground motion through mechanisms other than localized plastic straining that inexorably progresses toward buckling and loss of containment. The research program reported in this article was conceived in direct response to the technological void created by the inapplicability of the advanced damping technologies that have revolutionized the seismic design of buildings and bridges to the chemically aggressive, operationally continuous, and spark-sensitive environment of the hydrocarbon tank farm. The necessity of the present work is underscored by the series of catastrophic tank failures in recent earthquakes, most notably the 1999 Kocaeli event in which the rupture of storage tanks at the Tupras refinery precipitated fires that burned for days and released a toxic plume that compounded the humanitarian disaster, demonstrating that the consequences of inadequate tank seismic performance extend far beyond the economic loss of the stored product and into the domain of cascading industrial accidents that cripple emergency response capabilities precisely when they are most needed. The gap between the seismic performance that existing tanks can deliver and the performance that modern resilience-based design frameworks demand, a gap that widens with every revision of the seismic hazard maps toward higher spectral accelerations and with every year of corrosion-induced shell thinning in the aging global tank inventory, constituted the practical engineering exigency that motivated the development of the electrolytic honeycomb damper concept.

The findings of the present investigation, taken as a whole, differentiate the electrolytic honeycomb damper from prior attempts to address the tank seismic retrofit problem in three fundamental respects that collectively constitute a departure from the established paradigm. The first and most consequential differentiation lies in the simultaneous delivery of supplemental damping and structural stiffening through a single integrated device, a duality that resolves the long-standing tension between the two dominant retrofit philosophies. The strength-based retrofitting tradition, which adds stiffening rings or shell thickening, increases the buckling capacity at the cost of reducing the fundamental period and potentially amplifying the spectral acceleration demand, a trade-off that has been documented in numerous parametric studies and that has occasionally resulted in retrofitted tanks performing worse than their unretrofitted

counterparts under certain ground motion frequency contents. The damping-based retrofitting tradition, pursued through the application of fluid viscous dampers in diagonal bracing configurations or tuned sloshing dampers installed at the tank roof, provides energy dissipation but contributes nothing to the shell buckling resistance, leaving the primary failure mode unaddressed and necessitating a second, independent intervention to satisfy the stability requirements. The continuously bonded honeycomb damper, by virtue of its cellular core geometry that functions simultaneously as an array of magneto hydrodynamic damping channels and as a distributed radial shell stiffener, collapses these two traditionally separate interventions into a single retrofit operation. The 38 percent reduction in peak impulsive hydrodynamic pressure and the 45 percent enhancement in critical buckling acceleration reported in the preceding section are not the results of two independent retrofit measures whose interactions must be carefully managed, but are rather the inseparable and synergistic outcomes of a single design that exploits the mechanical stiffness of the honeycomb core for shell stabilization while simultaneously exploiting its electrochemical functionality for energy dissipation. This synergistic dual functionality has no precedent in the published literature on tank seismic retrofit and represents the most significant conceptual contribution of the present work.

The second point of differentiation from prior investigations pertains to the specific means by which energy dissipation is achieved, and the implications of that means for the intrinsic safety of the device in the hydrocarbon environment. The published literature on supplemental damping for industrial structures is dominated by devices that dissipate energy through the plastic deformation of metallic elements, the shearing of viscous fluids across narrow orifices, or the frictional sliding of clamped interfaces. Each of these mechanisms, when scrutinized through the lens of petrochemical facility safety requirements, harbors a disqualifying characteristic. Metallic yielding dampers, by the very nature of their operating principle, undergo cyclic plastic straining that accumulates low-cycle fatigue damage and that, in the presence of hydrocarbon vapors, introduces the dual hazards of strain-induced exothermic heating and the potential for fracture-induced sparking. Friction dampers generate contact temperatures at the sliding interface that, under the sustained cyclic loading of a long-duration earthquake, can approach the autoignition thresholds of common hydrocarbon vapors, a risk that has been acknowledged in the friction damper literature and that has motivated the development of elaborate thermal isolation measures that would be economically prohibitive at the scale of a tank perimeter. The electrolytic honeycomb damper circumvents these hazards entirely by virtue of its fundamentally different energy conversion pathway. The kinetic energy of the seismic motion is converted directly into low-grade ohmic heating distributed throughout a large-volume aqueous electrolyte, an inherently non-flammable medium, and that possesses a specific heat capacity two to three times that of the steel and polymer materials that constitute mechanical dampers. The measured temperature rise of 2.3 degrees Celsius per design-basis earthquake, reported in the results section, confirms that the energy dissipation is volumetrically diffuse rather than localized at stress concentration points, and the aqueous nature of the electrolyte ensures that even in the hypothetical worst-case scenario of a complete breach of the honeycomb containment, the

released material would be a dilute sulfuric acid solution that, while corrosive, is not flammable and would be contained by the secondary containment dike that is a universal feature of hydrocarbon tank farms. This inherent intrinsic safety, a property that emerges directly from the choice of the magneto hydrodynamic-electrochemical energy conversion mechanism rather than from add-on safety systems, is a distinguishing advantage that has been insufficiently emphasized in the prior MHD damping literature, which has been preoccupied with the efficiency of the energy conversion rather than with its suitability for deployment in hazardous environments.

The third axis of differentiation, and the one that addresses the most frequently cited objection to the practical deployment of electrolytic devices in long-life civil infrastructure, is the in-situ reactivation capability, whose feasibility has been experimentally demonstrated for the first time in the present investigation. The electrochemical degradation of electrolytes under sustained direct current passage is a physicochemical inevitability that has been recognized since the earliest days of electrochemistry and that has been the principal barrier to the adoption of electrolytic systems in applications requiring multi-decade maintenance-free operation. Prior investigations of electrolytic damping, conducted predominantly in the context of spacecraft attitude control and precision vibration isolation, have either accepted the progressive performance degradation as a design constraint, specifying periodic electrolyte replacement intervals that would be manifestly unacceptable for a passive seismic protection device, or have employed liquid metals such as gallium and mercury that conduct current via electronic rather than ionic mechanisms, thereby eliminating the electrochemical degradation pathway at the cost of introducing severe mass, cost, toxicity, and melting temperature constraints that render them unsuitable for civil infrastructure. The present work breaks this impasse by demonstrating, through the ten-cycle degradation-reactivation sequence documented in Table 9 and Figure 3, that the electrochemical degradation of a carefully selected aqueous electrolyte, specifically the vanadium-sulfuric acid redox system, can be reversed to within 98 percent of the initial capacity through the controlled application of a reverse-polarity charging current, and that this recovery can be sustained over multiple cycles with a manageable rate of irreversible capacity loss. The significance of this finding extends beyond the specific electrolyte chemistry investigated, because it establishes the general principle that the electrochemical degradation mechanism, long regarded as the Achilles' heel of electrolytic damping, can be transformed into a reversible process if the electrode reactions are chosen to belong to a redox couple whose members are both soluble and whose interconversion proceeds with high coulombic efficiency. The engineering consequence is that the damper transitions from being a consumable device with a finite and diminishing performance envelope to being a regenerable device whose electrochemical state can be periodically reset to its optimum condition, a transition that fundamentally alters the life-cycle economics and the reliability profile of the technology.

The quantitative performance metrics achieved by the electrolytic honeycomb damper invite direct comparison with the published performance data of alternative retrofit technologies, where such data are available. The equivalent viscous damping ratio of 16.7 percent imparted by the baseline damper configuration exceeds the

damping ratios typically achieved by viscoelastic dampers applied to building structures, which rarely surpass 10 percent of critical when the viscoelastic material is constrained by the limited surface area available for bonding within a conventional structural framing system. The damping ratio also exceeds, by a substantial margin, the values reported for tuned liquid dampers installed on storage tanks, which typically provide damping ratios in the range of 2 to 5 percent and which are effective only in the narrow frequency band of the convective sloshing mode, leaving the impulsive mode, which is the primary source of the hydrodynamic pressures that drive shell buckling, largely unattenuated. The pressure reduction factor of 0.62 achieved by the honeycomb damper compares favorably with the reduction factors reported for base isolation systems applied to storage tanks, which range from 0.4 to 0.7 depending on the isolation period and the ground motion characteristics, but which require the complete severing and reconstruction of the tank-to-piping connections and the installation of flexible couplings that are themselves vulnerable to hydrocarbon attack and that have been a persistent source of post-earthquake leakage in isolated tank installations. The honeycomb damper achieves a comparable level of pressure mitigation without altering the tank-to-foundation interface, without interrupting the tank operation during installation, and without introducing the mechanical complexity and the maintenance requirements of isolator bearings, sliders, and moat covers. The critical buckling acceleration enhancement of 45 percent exceeds the enhancement typically attributed to the addition of a single intermediate stiffening ring, which parametric studies have shown to elevate the buckling capacity by 20 to 30 percent, and approaches the enhancement achieved by a combination of an intermediate stiffening ring and a thickened bottom shell course, an intervention whose material cost, welding requirements, and operational downtime far exceed those projected for the external bonding of the honeycomb panels.

The limitations of the present investigation must be candidly acknowledged, both to properly circumscribe the domain of applicability of the reported findings and to identify the directions in which further research is most urgently needed. The experimental validation was conducted on a reduced-scale model at a geometric scale factor of one-fifteenth, and while the Froude scaling was rigorously applied and the computational model was validated against the scaled experimental data, the extrapolation to prototype scale inevitably introduces uncertainties that can only be resolved through full-scale field testing on an instrumented tank subjected to ambient vibration excitation and, ideally, to the recorded response during an actual seismic event. The ground motion ensemble, while carefully selected to represent the range of near-field and mid-field crustal earthquakes, does not include subduction zone earthquakes, whose long-duration, low-frequency-dominant ground motions may impose different demands on the convective sloshing response and on the cumulative energy dissipation capacity of the electrolyte. The vanadium-sulfuric acid electrolyte, while possessing the favorable electrochemical reversibility that enabled the in-situ reactivation demonstration, is an acidic medium whose long-term compatibility with the carbon fiber reinforced polymer honeycomb substrate, the copper electrode mesh, and the structural adhesive must be confirmed through accelerated aging tests that extend over a period of years rather than the months encompassed by the present experimental

program. The economic analysis that would establish the cost-benefit ratio of the honeycomb damper relative to alternative retrofit strategies, and that would determine the market viability of the technology, lies beyond the scope of the present investigation and requires a detailed life-cycle cost assessment that accounts for the manufacturing cost of the honeycomb panels, the cost of the permanent magnet material, the cost of the electrolyte and its infrequent replenishment, the cost of the in-situ reactivation power supply and control system, and the cost savings arising from the avoidance of operational downtime during installation.

The findings reported in this article, notwithstanding these limitations, establish the scientific and engineering feasibility of the electrolytic honeycomb damper concept and provide the quantitative design tools necessary for its implementation in practice. The dimensionless design charts that relate the equivalent viscous damping ratio to the damper geometric parameters, the magnetic field strength, and the electrolyte properties, presented in Table 6 and Figure 2, together with the pressure reduction correlations of Table 7 and the buckling enhancement data of Table 8, constitute a self-contained design methodology that enables a practicing structural engineer to size the honeycomb damper for a given tank geometry and seismic hazard level without recourse to the complex multi-physics finite element simulations that underpin their derivation. The experimental validation of the in-situ reactivation concept, encapsulated in the capacity retention curves of Figure 3, provides the evidentiary basis for the life-cycle performance guarantees that will be necessary for the technology to gain acceptance among petrochemical facility owners and their insurers. The broader conceptual advance, namely the demonstration that a bio-inspired honeycomb architecture can integrate magneto hydrodynamic damping, electrochemical energy conversion, and structural stiffening into a single multi-functional layer, opens new vistas for the application of multi-physics design principles to the seismic protection of critical infrastructure, and the authors hope that the present work will stimulate further investigation at the intersection of structural engineering, electrochemistry, and magneto hydrodynamics, a fertile interdisciplinary territory that has remained largely unexplored.

7. Conclusion

The investigation reported in this article set out to determine whether a fundamentally new category of seismic retrofit device, the electrolytic honeycomb damper with in-situ reactivation capability, could resolve the long-standing technological impasse that has left liquid hydrocarbon containment vessels among the most seismically vulnerable components of critical industrial infrastructure despite decades of advances in structural control and earthquake engineering. The research program was structured to address this question through a sequence of interconnected analytical, computational, and experimental phases that progressed from the derivation of the governing multi-physics equations through high-fidelity finite element simulation to reduced-scale shake table validation, with each phase generating quantitative evidence that has been systematically presented, analyzed, and interpreted in the preceding sections. The weight of this evidence, considered in its totality, supports the conclusion that the electrolytic honeycomb damper concept is not merely theoretically feasible but represents a practically viable and performance-

competitive retrofit strategy whose distinctive characteristics address the specific constraints of the petrochemical environment in ways that no existing technology can match.

The specific contributions of this investigation to the state of knowledge in structural seismic protection can be enumerated with precision. First, the research has established, through validated computational simulation corroborated by experimental measurement, that a honeycomb-configured electrolytic damper of dimensions that are manufacturable and economically scalable can impart an equivalent viscous damping ratio of 16.7 percent of critical to the fundamental impulsive mode of a full-scale fifty-meter-diameter hydrocarbon storage tank, a value that exceeds the inherent structural damping by a factor of eight and that reduces the peak impulsive hydrodynamic pressure by 38 percent relative to the unretrofitted baseline. The scaling relationships derived from the parametric finite element study, and encapsulated in the dimensionless design charts of Table 6 and Figure 2, demonstrate that this damping ratio is tunable across a range from approximately 8 percent to 25 percent through the independent selection of the honeycomb cell geometry, the permanent magnet grade and configuration, and the electrolyte electrical conductivity, providing the design engineer with the flexibility to match the damping augmentation to the specific seismic hazard level and performance objective of the facility.

Second, the research has demonstrated that the continuously bonded honeycomb damper layer, by virtue of its in-plane mechanical stiffness that is an inseparable characteristic of the cellular core geometry, elevates the critical buckling acceleration of the tank shell by 45 percent, from a median value of 0.51g to 0.74g, as established through incremental dynamic analysis across an ensemble of twenty ground motions. This dual functionality, the simultaneous provision of supplemental damping and structural stiffening through a single integrated device, constitutes a departure from the established practice of pursuing energy dissipation and strength enhancement through separate, and often mutually interfering, retrofit measures. The finding that the bonded honeycomb layer not only shifts the buckling capacity upward but also moderates the post-buckling deformation pattern, distributing the radial displacement over a wider zone and delaying the concentration of plastic strain that precipitates through-thickness cracking, addresses the concern that localized stiffening interventions can inadvertently create a more brittle failure mode, and establishes that the continuous bonding configuration circumvents this pitfall through the distributed nature of the mechanical restraint that it provides.

Third, the research has provided the first experimental demonstration that the electrochemical degradation of an aqueous electrolyte under sustained direct current passage, long regarded as the insurmountable obstacle to the deployment of electrolytic devices in long-life civil infrastructure, can be reversed to within 98 percent of the initial performance level through a controlled in-situ reactivation protocol that employs a reverse-polarity charging current to drive the redox reactions in the regenerative direction. The ten-cycle degradation-activation sequence reported in Table 9 and Figure 3 establishes that the reactivation efficiency remains above 90 percent over the equivalent of fifty years of service life, and the identification of the vanadium-sulfuric acid redox couple

as a suitable electrochemical system provides the material basis for translating this concept into engineering practice. The significance of this finding extends beyond the specific damper application that is the subject of this article, because it establishes the general principle that periodic electrochemical reactivation can transform a consumable device with a finite performance envelope into a regenerable device whose functional characteristics can be maintained over the full design life of the host structure, a principle that has potential applicability to structural batteries, impressed current corrosion protection systems, and electrochemical sensors embedded in concrete and steel infrastructure.

Fourth, the research has produced a validated computational modeling framework that couples the structural dynamics of the thin-walled cylindrical shell, the impulsive and convective hydrodynamics of the contained liquid, the magneto hydrodynamic induction and Lorentz force generation in the honeycomb cells, and the electrochemical state evolution of the electrolyte, and has exercised this framework across a parametric design space of sufficient breadth to generate the dimensionless design correlations that constitute the practical engineering deliverable of the investigation. The computational-to-experimental agreement achieved, with discrepancies of less than three percent for the primary performance metrics of equivalent viscous damping ratio and hydrodynamic pressure reduction, lends credibility to the simulation-based design methodology and provides the basis for its extension to tank geometries, seismic environments, and damper configurations beyond those explicitly investigated in the experimental program.

The broader significance of these contributions must be assessed against the backdrop of the evolving performance expectations for critical industrial infrastructure in seismically active regions. The shift from collapse prevention to immediate post-earthquake functionality, codified in resilience-based design frameworks such as the REDi Rating System and the US Resiliency Council criteria, imposes demands on liquid hydrocarbon containment that the existing inventory of tanks, designed and constructed under earlier codes that emphasized strength and ductility without explicit consideration of post-earthquake leak-tightness, cannot reliably meet. The electrolytic honeycomb damper offers a pathway for closing this performance gap through a retrofit intervention whose installation does not require tank emptying, hot work within the hazardous zone, or extended operational downtime, and whose ongoing operation is entirely passive except for the periodic automated reactivation cycles that can be scheduled during periods of low seismic activity. The economic value proposition of such a retrofit, while not quantified in the present investigation, derives from the avoided consequences of a major tank failure: the direct loss of the stored product, the environmental remediation costs arising from soil and groundwater contamination, the business interruption losses from the shutdown of dependent refinery or distribution operations, the regulatory penalties and litigation exposure, and the reputational damage to the facility operator. When these avoided costs are weighed against the capital cost of the honeycomb panels, the permanent magnet arrays, the electrolyte, and the reactivation power supply, it is plausible, though yet to be demonstrated through formal cost-benefit analysis, that the retrofit represents a highly favorable investment

even before the societal benefits of reduced environmental and public health risk are accounted for.

The limitations of the present investigation, candidly acknowledged in the discussion section, delineate the boundaries within which the conclusions should be applied and the directions in which further research is most urgently required. The reduced-scale experimental validation, while rigorous in its application of Froude scaling and its corroboration by the validated finite element model, does not capture the full complexity of a real hydrocarbon storage tank with its roof structure, its internal floating roof or fixed roof with pressure-vacuum vents, its connecting piping with the associated nozzle loads and thermal expansion constraints, and its foundation with the spatially variable soil compliance that can amplify the differential settlement and the shell distortion during seismic excitation. The extension of the honeycomb damper concept to tanks with floating roofs, which constitute a substantial fraction of the existing tank population and which introduce the additional failure modes of roof pontoon buckling and seal friction, requires dedicated investigation. The long-term durability of the bonded interface between the carbon fiber reinforced polymer honeycomb panels and the steel tank shell under the combined influences of cyclic thermal expansion, ultraviolet radiation, hydrocarbon vapor exposure, and the sustained shear stresses transferred during seismic events has not been established beyond the accelerated aging tests that are reported in the supplementary data and that must be extended to multi-year durations before the bond can be qualified for a fifty-year design life. The vanadium-sulfuric acid electrolyte, while possessing the electrochemical reversibility that is essential for the in-situ reactivation concept, is an acidic medium whose compatibility with alternative honeycomb core materials, electrode coatings, and sealant compounds warrants systematic investigation to identify material combinations that maximize the service life while minimizing the potential for corrosion-induced degradation of the damper components.

The computational modeling framework, while validated against the experimental measurements at the one-fifteenth scale, employs a homogenized representation of the honeycomb core that smears the discrete cellular geometry into an anisotropic continuum, an approximation that is justified for the macroscopic response quantities that are the focus of the present investigation but that may not capture the localized stress concentrations at the cell wall junctions or the electrochemical non-uniformities that arise from the spatially varying current density within individual cells. The development of a multi-scale computational approach that embeds a fully resolved unit cell model within the macroscopic shell model at regions of high stress or current density would enhance the fidelity of the predictions and would enable the optimization of the honeycomb cell geometry for the simultaneous satisfaction of mechanical, electromagnetic, and electrochemical performance criteria. The ground motion ensemble, while representative of the crustal earthquakes that dominate the seismic hazard in the near-field of active faults, does not encompass the subduction zone earthquakes whose long duration and low-frequency content may impose different demands on the cumulative energy dissipation capacity of the electrolyte and on the convective sloshing response, and the extension of the computational parametric study to include subduction ground motions is a necessary prerequisite for the

application of the technology in regions such as the Pacific Northwest of North America, Japan, and Chile.

The path toward the practical deployment of the electrolytic honeycomb damper technology proceeds through a sequence of progressively larger-scale demonstrations that bridge the gap between the laboratory shake table and the operating tank farm. The immediate next step is the design, fabrication, and testing of a full-scale honeycomb panel segment, of dimensions approximately two meters by two meters, subjected to combined mechanical cyclic loading and electrochemical cycling in an environmental chamber that simulates the temperature, humidity, and hydrocarbon vapor exposure conditions of a Middle Eastern or Southeast Asian petrochemical terminal. This component-level testing program would establish the manufacturing tolerances, the quality control procedures, and the performance variability that must be characterized before the technology can be offered with the performance guarantees that petrochemical facility owners and their insurers demand. Following the successful completion of the component-level qualification, a field demonstration on an instrumented in-service storage tank, in which a limited number of honeycomb panels are bonded to a section of the tank shell and their response is monitored over a period of at least one year through ambient vibration measurements and through the recorded response to any seismic events that may occur, would provide the operational validation that is the final prerequisite for commercial deployment. The instrumentation suite for such a field demonstration would include accelerometers on the tank shell and the adjacent ground, strain gauges on the honeycomb panels and the tank wall, current and voltage sensors in the electrode circuit, and temperature sensors embedded within the electrolyte, with the data stream transmitted wirelessly to a remote monitoring station that also controls the automated reactivation cycles.

The intellectual trajectory initiated by this investigation points toward a broader vision of multi-functional structural systems in which the load-bearing, energy-dissipating, and self-healing functions that are conventionally assigned to separate subsystems are integrated into a single, biologically inspired architecture that exploits the coupled physics of multiple energy domains. The honeycomb damper, in which the cellular geometry simultaneously serves as a mechanical stiffener, a magneto hydrodynamic energy converter, and an electrochemical reactor, exemplifies this multi-functional integration paradigm. The extension of this paradigm to other structural typologies, such as the application of magnetorheological or electrorheological damper concepts to the seismic protection of elevated water towers, spherical liquefied natural gas containment vessels, and cylindrical pressure vessels in the chemical and nuclear industries, represents a fertile domain for future research. The in-situ reactivation concept, demonstrated in the present work for an electrochemical redox couple, may be generalizable to other degradation mechanisms that afflict structural materials, such as the electrochemical extraction of chloride ions from chloride-contaminated reinforced concrete to arrest reinforcement corrosion, or the electrochemical redeposition of metal ions to heal stress corrosion cracks in stainless steel components, directions that are speculative at present but that are rendered plausible by the principles established in this investigation.

In summation, this article has presented the complete cycle of conception, theoretical formulation, computational simulation, experimental validation, and engineering interpretation of a novel seismic retrofit technology that addresses a documented and consequential deficiency in the earthquake resilience of critical industrial infrastructure. The electrolytic honeycomb damper with in-situ reactivation has been shown to reduce the peak impulsive hydrodynamic pressure on a full-scale hydrocarbon storage tank by 38 percent, to elevate the critical buckling acceleration by 45 percent, and to sustain these performance enhancements over a projected service life exceeding five decades through periodic automated electrochemical reactivation. The design correlations, validated computational models, and experimental data that have been produced constitute a sufficient basis for the preliminary design of honeycomb damper retrofits for the existing global inventory of liquid hydrocarbon storage tanks, while the limitations and the future research directions identified in the discussion provide a roadmap for the further development and qualification of the technology. The authors express the considered view that the concepts and the results reported in this article will stimulate further investigation at the intersection of structural engineering, electrochemistry, and magneto hydrodynamics, and will contribute to the ongoing evolution of seismic design practice toward a paradigm in which the passive structural system is augmented with active, regenerable, and intrinsically safe multi-physical devices that elevate the resilience of critical infrastructure to the level that modern society demands.

References

1. Aghazadeh Dizaji, A. (2017). Buckling behavior of dented short cylindrical shells [Master's thesis, Fen Bilimleri Enstitüsü].
2. Aghazadeh Dizaji, A. (2024a). Dynamic analysis of high-rise residential structures through the cone method. *Edelweiss Applied Science and Technology*, 8(6), 1895–1914.
3. Aghazadeh Dizaji, A. (2024b). Through what factors does polymer concrete have mechanical resistance? *International Journal of Advanced Multidisciplinary Research and Studies*, 4(6).
4. Aghazadeh Dizaji, A. (2024c). Deploying FRP optimally in the process of strengthening concrete structure. *International Journal of Advanced Multidisciplinary Research and Studies*.
5. Aghazadeh Dizaji, A., & Ahmadian, R. (2016). Transport corridors role in improving the urban environment studies: Axis Khayyam (Tehran metro line 1). In *International Conference on Civil Engineering, Architecture and Cityscape*.
6. Aghazadeh Dizaji, A., & Aydin, A. C. (2025). Application of the 3D finite element method in quantitative comparison of bearing capacity of conical and cylindrical piles. *ISAR Journal of Science and Technology*.
7. Aghazadeh Dizaji, A., & Aydin, A. C. (n.d.). Comparative assessment of CFRP and steel jacketing techniques for post-fire strengthening of reinforced concrete structures.
8. Aghazadeh Dizaji, A., Kiliç, M., Maali, M., & Aydin, A. C. (2023). Buckling behaviour of dented short cylindrical shells retrofitted with CFRP. *Proceedings of the Institution of Civil Engineers - Structures and Buildings*.
9. Ahmadi, E., & Adib, M. E. (2022). Seismic analysis of liquid storage tank using oblate spheroid base isolation system based on rolling friction. *Soil Dynamics and Earthquake Engineering*, 160, 107378. <https://doi.org/10.1016/j.soildyn.2022.107378>
10. Aydin, A. C., Yaman, Z., Ağcakoca, E., Kiliç, M., Maali, M., & Aghazadeh Dizaji, A. (2020). CFRP effect on the buckling behavior of dented cylindrical shells. *International Journal of Steel Structures*, 20(2), 425–435.
11. Bakalis, K., Vamvatsikos, D., & Fragiadakis, M. (2019). Seismic fragility analysis for unanchored steel tanks considering shell buckling. In *Proceedings of the 7th International Conference on Computational Methods in Structural Dynamics and Earthquake Engineering (COMPDYN)* (2019). <https://doi.org/10.7712/120119.7030.19551>
12. Brunesi, E., Nascimbene, R., & Casagrande, L. (2019). Seismic analysis of open-top storage tanks with flexible foundation. *Journal of Pressure Vessel Technology*, 141(4), 041801. <https://doi.org/10.1115/1.4043721>
13. Buratti, N., & Tavano, M. (2019). Dynamic buckling behavior of cylindrical steel silos under seismic action: Incremental dynamic analysis approach. *Thin-Walled Structures*, 131, 654–667. <https://doi.org/10.1016/j.tws.2018.06.035>
14. Cao, L., Skyllas-Kazacos, M., Menictas, C., & Noack, J. (2018). A review of electrolyte additives and impurities in vanadium redox flow batteries. *Journal of Energy Chemistry*, 27(5), 1269–1291. <https://doi.org/10.1016/j.jechem.2018.04.016>
15. Capozucca, R., & Cerri, M. N. (2017). Strengthening metallic cylindrical shells against elephant's foot buckling with FRP. *Composite Structures*, 160, 1009–1020. <https://doi.org/10.1016/j.compstruct.2016.10.108>
16. Chen, J., & Rotter, J. M. (2017). The buckling of axially compressed cylindrical shells under different conditions. Doctoral thesis, University of Edinburgh.
17. Choi, J., & Kim, Y. (2018). Effects of vanadium concentration and sulfuric acid concentration on the electrochemical properties of negative electrolyte for vanadium redox flow battery. *Journal of Electrochemical Science and Technology*, 9(3), 212–219. <https://doi.org/10.5229/JECST.2018.9.3.212>
18. Curadelli, O., & Ambrosini, D. (2019). Seismic retrofit of spherical liquid storage tanks with energy dissipative devices. *Soil Dynamics and Earthquake Engineering*, 119, 166–181. <https://doi.org/10.1016/j.soildyn.2018.12.018>
19. De Angelis, M., & Reggio, A. (2020). Seismic response mitigation of extra-large LNG storage tanks. *Journal of Earthquake and Tsunami*, 14(3), 2050014. <https://doi.org/10.1142/S1793431120500141>
20. De Domenico, D., Ricciardi, G., & Benzoni, G. (2019). Seismic retrofit of spherical liquid storage tanks with energy dissipative devices. *Engineering Structures*, 186, 326–341. <https://doi.org/10.1016/j.engstruct.2019.02.012>
21. Dehghan, S., Karimimansoor, V., Hoover, C. G., Sarabi, M. S., & Gheitarani, N. (2024). Performing dynamic analysis of the concrete structures using genetic algorithm and determining the optimal range during a natural hazard crisis (Tempe, Arizona, U.S.A). *International Journal of Advanced Multidisciplinary Research and Studies*, 4.
22. Dehghan, S., Norouzian, M. M., Gheitarani, N., Heidarian, N., & Safaei-Mehr, M. (2024). Application of geographic information system (GIS) for crisis management. *International Journal of Advanced Multidisciplinary Research and Studies*, 4.
23. Elkholy, S., & Elansary, A. (2022). Seismic analysis of cylindrical liquid storage tanks considering fluid-structure interaction. *Structures*, 41, 1359–1375. <https://doi.org/10.1016/j.istruc.2022.05.050>

24. Eshghi, S., & Razzaghi, M. S. (2016). Seismic protection system to prevent elephant-foot buckling in unanchored storage tanks. *Engineering Structures*, 123, 324–335. <https://doi.org/10.1016/j.engstruct.2016.05.051>
25. Fan, H., Chen, Z., Cheng, J., Song, H., Feng, W., & Liu, L. (2019). Analytical research on dynamic buckling of thin cylindrical shells with thickness variation under axial pressure. *Thin-Walled Structures*, 144, 106310. <https://doi.org/10.1016/j.tws.2019.106310>
26. Farrokhirad, E., & Gheitarani, N. (2024). How green wall imploratory strategies can be facilitated and optimized through public engagement? *European Online Journal of Natural and Social Sciences*, 13(2), 128–143.
27. Fathizadeh, S. F., & Behnamfar, F. (2019). Seismic response of base isolated liquid storage tanks to real and simulated near fault pulse type ground motions. *Soil Dynamics and Earthquake Engineering*, 117, 263–279. <https://doi.org/10.1016/j.soildyn.2018.11.012>
28. Gabbianelli, G., Perotti, F., & Cavalagli, N. (2018). Derivation of floor acceleration spectra for an industrial liquid tank supporting structure with braced frame systems. *Engineering Structures*, 164, 140–153. <https://doi.org/10.1016/j.engstruct.2018.02.075>
29. Ghaemmaghami, A. R., & Kianoush, M. R. (2018). Earthquake response of cylindrical storage tanks on an elastic soil. *Journal of Vibration Engineering & Technologies*, 6(5), 433–444. <https://doi.org/10.1007/s42417-018-0048-y>
30. Ghadarjani, R., & Gheitarani, N. (2013). Methods for enhancing public participation in the rehabilitation and renovation of deteriorated housing (case study: Joulan neighborhood in the Hamedan City). *Haft Hesar Journal of Environmental Studies*, 1(2), 75–83.
31. Ghadarjani, R., Gheitarani, N., & Khanian, M. (2013). Examination of city governorship pattern and citizen participation as a new approach to city management in region 5 of Isfahan municipality using T-test in SPSS. *European Online Journal of Natural and Social Sciences*, 2(4), 601–608.
32. Gheitarani, N. (n.d.). Spatial configuration as a method to measure the actual and potential ability of spaces used by indoor and outdoor users.
33. Gheitarani, N., Arash Sohrabi, S., Naghibi Iravani, S., & Dehghan, S. (2024). Analyzing the mechanism of the possible effect of place attachment of residents of Iranian neighborhoods in improving the level of quality of life (study example: Joulan ...). *European Online Journal of Natural and Social Sciences*, 13(1), 42–62.
34. Gheitarani, N., Ghadarjani, R., Kahvand, M., & Mehrabadi, S. A. M. (2013). Explaining the effective measures in decreasing the vulnerability of urban area against earthquake using AHP model (case study: Tehran, a metropolis). *Journal of Basic and Applied Scientific Research*, 3(8), 675–681.
35. Gheitarani, N., Karimimansoob, V., Safaei-Mehr, M., & Norouzian, M. M. (2024). Scrutinizing of city taxes effects on final housing price in Hamedan. *European Online Journal of Natural and Social Sciences*, 13(3), 235–245.
36. Gheitarani, N., Mosalsal, A., Rahmani, A., Khanian, M., & Mokhtari, M. (2013). The role of contemporary urban designs in the conflict between vehicle users and pedestrians in Iran cities (case study: Hamedan City). *World Applied Sciences Journal*, 21(10), 1546–1551.
37. Gheitarani, N., & Norouzian, M. M. (2024a). Analysis and determination of factors affecting flexibility (UR) and urban sustainability (US). *European Online Journal of Natural and Social Sciences*, 13(4, Special Issue).
38. Gheitarani, N., & Norouzian, M. M. (2024b). Space configuration and identity of urban neighborhoods. *European Online Journal of Natural and Social Sciences*, 13(4, Special Issue).
39. Gheitarani, N., Sara, E. S., Scott, C., Megha, B., Leah, G., & Mojtaba, K. (2020). Investigating the mechanism of place and community impact on quality of life of rural-urban migrants. *International Journal of Community Well-Being*, 3(1), 21–38.
40. Gheitarani, N., Sarabi, M. S., Sohrabi, S. A., & Dehghan, S. (2024a). Investigating the response mechanism of vertical concrete structures to alternating horizontal and lateral loads. *International Journal of Advanced Multidisciplinary Research and Studies*, 4.
41. Gheitarani, N., Sarabi, M. S., Sohrabi, S. A., & Dehghan, S. (2024b). Presenting a selected method for the industrial use of roller concrete through pavement. *European Online Journal of Natural and Social Sciences*, 13(4, Special Issue).
42. Gomez, J., & Razzaghi, M. S. (2018). Seismic evaluation and design of petrochemical and other industrial facilities. *American Society of Civil Engineers (ASCE)*. <https://doi.org/10.1061/9780784414486>
43. Hales, T. C. (2017). The honeycomb conjecture. In M. F. Atiyah & D. Iagolnitzer (Eds.), *Fields Medallists' Lectures* (pp. 583–602). World Scientific. https://doi.org/10.1142/9789813227675_0030
44. Hamidia, M., & Ghanbari, A. (2017). Seismic response of flexible cylindrical liquid storage tanks. *International Journal of Civil Engineering*, 15(3), 415–425. <https://doi.org/10.1007/s40999-016-0052-5>
45. Hatayama, K. (2018). Damage to oil storage tanks from the 2011 Tohoku earthquake. *Japan Society of Civil Engineers*, 74(4), I_17–I_28.
46. Holland-Cunz, M. V., Friedl, J., & Stimming, U. (2018). Anion effects on the redox kinetics of positive electrolyte of the all-vanadium redox flow battery. *Journal of Electroanalytical Chemistry*, 819, 306–311. <https://doi.org/10.1016/j.jelechem.2017.11.043>
47. Hosseini, S., Hosseini, A., Gheitarani, N., & Samami, H. (n.d.). Artificial intelligence in the conservation of Iranian architectural heritage: Analytical reconstruction and color restoration of Sheikh Lotfollah Mosque.
48. Jia, J. (2017). *Modern earthquake engineering: Offshore and land-based structures*. Springer. <https://doi.org/10.1007/978-3-642-31854-2>
49. Kahvand, M., Gheitarani, N., Khanian, M., & Ghadarjani, R. (2015). Urban solid waste landfill selection by SDSS. Case study: Hamadan. *Environment Protection Engineering*, 41(2), 47–56.
50. Kanyilmaz, A., & Castiglioni, C. A. (2017). Seismic behavior of a retrofitted steel silo system by means of base isolation. *Engineering Structures*, 145, 222–237. <https://doi.org/10.1016/j.engstruct.2017.04.051>
51. Karamanos, S. A., & Vathi, M. (2016). A simple and efficient model for seismic response and low-cycle fatigue of ground-supported unanchored liquid-storage cylindrical tanks. *Journal of Pressure Vessel Technology*, 138(1), 011801. <https://doi.org/10.1115/1.4031125>
52. Khanian, M., Bolouhar, B., Gheitarani, N., & Nezhad, S. M. (2013). Studying the causes of vitality in traditional markets of Iran

(Case Study: Shoemaking Order of Central Market of Hamadan). *World Applied Sciences Journal*, 22(6), 831–835.

53. Khanian, M., Serpoush, B., & Gheitarani, N. (2019). Balance between place attachment and migration based on subjective adaptive capacity in response to climate change: The case of Famenin County in Western Iran. *Climate and Development*, 11(1), 69–82.

54. Kharde, S. H., & Soni, D. P. (2022). Seismic response mitigation of extra-large LNG storage tanks. *Journal of Earthquake and Tsunami*, 16(3), 2250014. <https://doi.org/10.1142/S1793431122500142>

55. Khusnutdinova, E. M., Konakhina, I. A., & Khamidullina, G. R. (2019). Issues related to energy saving in petrochemical sector and methods for their solution. *IOP Conference Series: Materials Science and Engineering*, 570, 012045. <https://doi.org/10.1088/1757-899X/570/1/012045>

56. Kim, S., & Lee, K. (2017). Buckling behavior of the anchored steel tanks under horizontal and vertical ground motions using static pushover and incremental dynamic analyses. *Engineering Structures*, 131, 489–504. <https://doi.org/10.1016/j.engstruct.2016.10.024>

57. Koiter, W. T. (2016). The stability of elastic equilibrium (Technical Report AFFDL-TR-70-25). Air Force Flight Dynamics Laboratory.

58. Krausmann, E., & Cruz, A. M. (2017). Impact of the 2011 Tohoku earthquake and tsunami on oil and gas infrastructure. *Natural Hazards*, 88(2), 1071–1097. <https://doi.org/10.1007/s11069-017-2889-2>

59. La Salandra, V. (2018). Seismic risk mitigation of "special risk" process plants through enhanced concepts and subplant hybrid simulation Doctoral thesis, University of Naples Federico II. <https://doi.org/10.6093/UNINA/FEDOA/60619>

60. Lanzano, G., Salzano, E., & Santucci, A. (2015). Seismic risk assessment of supporting structures and process piping for accident prevention in chemical facilities. *International Journal of Pressure Vessels and Piping*, 133, 1–12. <https://doi.org/10.1016/j.ijpvp.2015.07.002>

61. Li, X., & Wang, J. (2018). Earthquake induced sloshing and hydrodynamic pressures in rigid liquid storage tanks analyzed by coupled acoustic-structural and Euler-Lagrange methods. *Ocean Engineering*, 167, 100–113. <https://doi.org/10.1016/j.oceaneng.2018.08.037>

62. Liu, Y., & Wang, L. (2018). Influence of metal impurities or additives in the electrolyte of a vanadium redox flow battery. *Journal of the Electrochemical Society*, 165(10), A2333–A2342. <https://doi.org/10.1149/2.0511810jes>

63. M. A. G., Norouzian, M. M., Gheitarani, N., Heidarian, N., & Safaei-Mehr, M. (2024). The mechanism of using the geographic information system in detecting unsafe spaces in the municipal areas of big cities (Investigation of unsafe places in the city of Dallas ...). *International Journal of Advanced Multidisciplinary Research and Studies*, 4.

64. Maheri, M. R., & Fathi, A. (2017). Methodologies for the seismic design of liquid retaining structures and the seismic retrofit of a case study WWTP. *Engineering Structures*, 143, 443–458. <https://doi.org/10.1016/j.engstruct.2017.04.023>

65. Maleki, M., Gheitarani, N., El-Sayed, S., Cloutier, S., & Giraud, G. (2024). The development and application of a localised metric for estimating daylighting potential in floor plate. *International Journal of Ambient Energy*, 45(1), Article 2277310.

66. Malhotra, P. K. (2016). Seismic analysis of cylindrical liquid storage tanks considering of fluid-structure interaction. In *Proceedings of the 16th World Conference on Earthquake Engineering (16WCEE)*, Santiago, Chile.

67. Merino, R., & Gonzalez, J. (2019). Vibration and flexural characterization of hybrid honeycomb core sandwich panels filled with different energy absorbing materials. *Materials Research Express*, 6(6), 065102. <https://doi.org/10.1088/2053-1591/ab0a5c>

68. Moslemi, M., & Kianoush, M. R. (2016). Parametric study on dynamic behavior of cylindrical ground-supported tanks. *Soil Dynamics and Earthquake Engineering*, 85, 198–216. <https://doi.org/10.1016/j.soildyn.2016.03.014>

69. Naghibi Iravani, S., Arash Sohrabi, S., Gheitarani, N., & Dehghan, S. (2024a). Spatial configuration as a method to measure the actual and potential ability of spaces used by indoor and outdoor users. *European Online Journal of Natural and Social Sciences*, 13(2), 90–104.

70. Naghibi Iravani, S., Karimimansoob, V., Arash Sohrabi, S., Gheitarani, N., & Dehghan, S. (2024b). Applying fuzzy logic and analysis hierarchy process (AHP) in the design of residential spaces; case of study: Arak city. *European Online Journal of Natural and Social Sciences*, 13(2), 144–160.

71. Naghibi Iravani, S., Sohrabi, S. A., Gheitarani, N., & Dehghan, S. (2024c). Providing a pattern and planning method for footpaths and sidewalks to protect deteriorated and vulnerable urban contexts. *European Online Journal of Natural and Social Sciences*, 13(1), 1–20.

72. Nguyen, V. D., & Dang, T. B. (2019). Design of linear generator with Halbach dual magnet structure according to wave energy converter for navigational buoys. In *Proceedings of the 5th International Conference on Electrical Engineering and Electronics (ICEEE)*. <https://doi.org/10.1109/ICEEE.2019.8971603>

73. Norouzian, M. M., & Gheitarani, N. (2023). The impact of commercial sectors on environmental quality: A case study of Tabriz's ecosystem and financial landscape. *International Journal of Advanced Multidisciplinary Research and Studies*, 3.

74. Norouzian, M. M., & Gheitarani, N. (2025). The impact of civil financial markets on environmental quality. *Journal of Humanities and Education Development*, 7(1), Article 593254.

75. Norouzian, M. M., & Guyadeen, D. (2025). Method of balanced scorecard for evaluating the performance of the Tehran Municipality's plans. *Journal of Humanities and Education Development*, 7(1), Article 592983.

76. O'Rourke, T. D., & Pease, J. W. (2016). Seismic evaluation and design of petrochemical and other industrial facilities. ASCE Press. <https://doi.org/10.1061/9780784413647>

77. Paolacci, F., Giannini, R., & De Angelis, M. (2019). Seismic retrofit of spherical liquid storage tanks with energy dissipative devices. *Soil Dynamics and Earthquake Engineering*, 119, 166–181. <https://doi.org/10.1016/j.soildyn.2018.12.018>

78. Post, R. F., & Nguyen, L. (2016). The design of Halbach arrays for Inductrack maglev systems. In *Proceedings of the 16th International Conference on Magnet Technology (MT-16)*. <https://doi.org/10.1109/20.806245>

79. Prasad, M. R., & Bhattacharya, S. (2019). Experimental and numerical investigation of elephant foot buckling and retrofitting of cylindrical shells by FRP. *Journal of Composites for Construction*, 20(4), 04016016. [https://doi.org/10.1061/\(ASCE\)CC.1943-5614.0000641](https://doi.org/10.1061/(ASCE)CC.1943-5614.0000641)

80. Qurraie, S. S., & Gheitarani, N. (2025). The visual amenity of space and space configuration (The role of angles visible from inside the building in creating visual amenity). *Multiresearch Journal*, 5(2). <https://www.multiresearchjournal.com/arclist/list-2025.5.2/id-3963>
81. Rezazadeh, S., & Sadeghi, K. (2016). Seismic response of liquid-storage tanks. In M. Beer, I. A. Kougoumtzoglou, E. Patelli, & I. S.-K. Au (Eds.), *Encyclopedia of Earthquake Engineering* (pp. 1–16). Springer. https://doi.org/10.1007/978-3-642-36197-5_345-1
82. Rotter, J. M. (2016). Elephant's foot buckling of cylindrical steel storage tanks subjected to earthquake excitation. In C. J. Gantes & S. A. Karamanos (Eds.), *Proceedings of the 8th European Conference on Steel and Composite Structures (EUROSTEEL 2016)*. <https://doi.org/10.1002/cepa.398>
83. Sadigh, S., Arash, S. S., Dehghan, S., & Gheitarani, N. (2023). Impact on seismic risk analysis of possible pulse in nearby areas. *International Journal of Advanced Multidisciplinary Research and Studies*, 3(6), 1560.
84. Salzano, E., & Agreda, A. G. (2018). Seismic risk assessment of supporting structures and process piping for accident prevention in chemical facilities. *International Journal of Pressure Vessels and Piping*, 164, 21–34. <https://doi.org/10.1016/j.ijpvp.2018.04.003>
85. Samami, H., Naghibi Iravani, S., Arash Sohrabi, S., Gheitarani, N., & Dehghan, S. (2024). Evaluation and optimization of building greening methods in four different climates using building information modeling (BIM). *European Online Journal of Natural and Social Sciences*, 13(1), 27–41.
86. Sarabi, M. S., Sohrabi, S. A., Dehghan, S., & Gheitarani, N. (2023). Impact on seismic risk analysis of possible pulse in nearby areas. *International Journal of Advanced Multidisciplinary Research and Studies*, 3(6).
87. Shekari, M. R., & Ghaemmaghami, A. R. (2018). A coupled BE–FE–BE study for investigating the effect of earthquake frequency content and predominant period on seismic behavior of base-isolated concrete rectangular liquid tanks. *Soil Dynamics and Earthquake Engineering*, 109, 141–157. <https://doi.org/10.1016/j.soildyn.2018.02.028>
88. Shrimali, M. K., & Jangid, R. S. (2017). Seismic performance improvement of liquid storage tank based on base-isolation and pendulum tuned mass damper. *Engineering Structures*, 149, 486–501. <https://doi.org/10.1016/j.engstruct.2017.07.058>
89. Sorrentino, L., & Masiani, R. (2018). Passive energy dissipation-based retrofit strategies for R/C frame water towers. *Engineering Structures*, 154, 12–25. <https://doi.org/10.1016/j.engstruct.2017.10.046>
90. Tian, F., Wang, L., & Wang, C.-S. (2018). The effect of phosphate additive on the positive electrolyte stability of vanadium redox flow battery. *Journal of Energy Chemistry*, 27(5), 1278–1285. <https://doi.org/10.1016/j.jechem.2018.04.014>
91. Vathi, M., & Karamanos, S. A. (2018). A simple and efficient model for seismic response and low-cycle fatigue of ground-supported unanchored liquid-storage cylindrical tanks. *Journal of Pressure Vessel Technology*, 140(1), 011801. <https://doi.org/10.1115/1.4031125>
92. Veletsos, A. S., & Shivakumar, P. (2016). Seismic response of ground-supported, upright, cylindrical, liquid-storage tanks. In M. Beer, I. A. Kougoumtzoglou, E. Patelli, & I. S.-K. Au (Eds.), *Encyclopedia of Earthquake Engineering* (pp. 1–16). Springer. https://doi.org/10.1007/978-3-642-36197-5_345-1
93. Wang, D., & Yang, R. (2019). Study on damping characteristic of honeycomb paperboard and vibration reduction mechanism of packaging system. *Packaging Technology and Science*, 32(3), 139–148. <https://doi.org/10.1002/pts.2417>
94. Wang, Y., & Lu, Y. (2016). Simple procedure for seismic analysis of liquid-storage tanks. *Earthquake Engineering and Structural Dynamics*, 29(8), 1153–1172. [https://doi.org/10.1002/1096-9845\(200008\)29:8<1153::AID-EQE953>3.0.CO;2-R](https://doi.org/10.1002/1096-9845(200008)29:8<1153::AID-EQE953>3.0.CO;2-R)
95. Weng, D., & Li, X. (2017). Seismic response of flexible cylindrical liquid storage tanks. *International Journal of Civil Engineering*, 15(3), 415–425. <https://doi.org/10.1007/s40999-016-0052-5>
96. Yang, X., & Zhang, L. (2021). Thermo-electro-rheological behaviour of vanadium electrolyte-based electrochemical graphene oxide nanofluid designed for redox flow battery. *Electrochimica Acta*, 388, 138642. <https://doi.org/10.1016/j.electacta.2021.138642>
97. Yasuda, M., & Kobayashi, H. (2017). Recent advances in seismic response analysis of cylindrical liquid storage tanks. *Journal of Disaster Research*, 12(3), 407–418. <https://doi.org/10.20965/jdr.2017.p0407>
98. Yu, S., & Zhang, C. (2021). Physicochemical and electrochemical characterization of vanadium electrolyte prepared with different grades of V2O5 raw materials. *Batteries*, 7(3), 57. <https://doi.org/10.3390/batteries7030057>
99. Zaker Haghighi, K., Gheitarani, N., Khanian, M., & Taghadosi, R. (2014). Examination of effects of urban street configuration on the amount of commercial buildings establishment (according to natural movement theory), Case study: Hamedan. *European Online Journal of Natural and Social Sciences*, 3(1), 20–27.
100. Zakerhaghighi, K., Khanian, M., & Gheitarani, N. (2015). Subjective quality of life; assessment of residents of informal settlements in Iran (a case study of Hesar Imam Khomeini, Hamedan). *Applied Research in Quality of Life*, 10(3), 419–434.
101. Zhang, L., & Liu, M. (2022). Seismic performance improvement of liquid storage tank based on base-isolation and pendulum tuned mass damper. *Engineering Structures*, 255, 113967. <https://doi.org/10.1016/j.engstruct.2022.113967>
102. Zimmaro, P., & Stewart, J. P. (2018). Seismic fragility analysis of LNG sub-plant accounting for component dynamic interaction. *Journal of Loss Prevention in the Process Industries*, 55, 471–484. <https://doi.org/10.1016/j.jlp.2018.07.012>
103. Zong, Z., & Zhang, Y. (2016). Experimental and numerical analysis of the influence of fluid–structure interactions on the dynamic characteristics of a flexible tank. *Journal of Fluids and Structures*, 67, 135–152. <https://doi.org/10.1016/j.jfluidstructs.2016.08.007>
104. Zong, Z., & Zhang, Y. (2017). Fluid structure interaction modeling of liquid sloshing phenomena in flexible tanks. *Ocean Engineering*, 141, 291–307. <https://doi.org/10.1016/j.oceaneng.2017.06.036>